



130G HARD-MOUNT WASHER LIGHT DRY EXTRACTION

OUR BEST VALUE WASHER.
BETTER THAN EVER.

With a dual language display and the ability to store up to 48 wash programs, Compass Pro gives your operators an effortless laundry experience. Loaded with energy and water-saving technology, this 130G washer will help you optimize your laundry operation.



INNOVATIVE TECHNOLOGY

Increased extraction power delivers speed in more than a name.

130 G-FORCE SPIN

We've upgraded our entry-level washer to 130G force spin. More water extracted during the spin cycle leads to shorter dry times and longer linen life.

SUPER BALANCE

Maintain high-spin performance and extend the life of your washer with our Super Balance technology.

Don't wash efficiency down the drain. Reduce costs — automatically.

ULTRA FLAT DRAIN VALVE

Other washers waste up to 1 ½ gallons of water every wash. Our ultra flat drain valve helps us save 97% in dead water vs our competitors.

EFFICIENT DOSING

Reduce chemical costs by over 30%. Our dosing technology weighs each load and adds the optimum volume of soap and other chemicals to achieve the best wash results.

Optimize your on-premises laundry operation.

COMPASS PRO

With a dual-language display and 48 programmable wash options, Compass Pro allows laundry operations to optimize their laundry room and eliminate user error.

ERGONOMIC DESIGN

Electrolux Professional washers are certified to international standards of ergonomics, making your laundry room a healthier and more productive workplace.

	ELD-620	ELD-625	ELD-630	ELD-645	ELD-665	ELD-685
DRY WEIGHT CAPACITY (LB/KG)	20 9	25 11	30 14	45 20	65 29	85 39
WIDTH (IN/MM)	26 660	28 ¾ 720	28 ¾ 720	29 ½ 750	32 ¼ 830	35 ¼ 910
DEPTH (IN/MM)	28 ¾ 725	27 ¾ 700	31 ¼ 790	36 915	40 ¾ 1030	43 ¾ 1115
HEIGHT (IN/MM)	44 ¼ 1135	48 ¾ 1220	48 ¾ 1220	52 ¼ 1345	56 ¾ 1430	57 ¼ 1465
HEIGHT TO BOTTOM OF DOOR (IN/MM)	14 ¾ 360	14 ¾ 370	14 ¾ 370	17 ¾ 440	18 ½ 470	19 ¾ 505
DOOR OPENING DIAMETER (IN/MM)	12 ¾ 310	14 ¾ 365	14 ¾ 365	15 ¾ 395	17 ¾ 435	17 ¾ 435
CYLINDER VOLUME (FT ³ /L)	3 85	3.7 105	4.6 130	6.4 180	8.8 250	11.7 330
DRAIN OUTLET DIAMETER (IN/MM)	3 75	3 75	3 75	3 75	3 75	3 75
HEIGHT TO CENTERLINE OF DRAIN (IN/MM)	4 ¾ 105	4 ¾ 105	4 ¾ 105	4 ¾ 105	4 ¾ 105	4 ¾ 103
EXTRACTION (G-FORCE)	130G	130G	130G	130G	130G	130G
DYNAMIC LOAD (LB/KN)	330 +/- 640 1.5+/-2.9	420+/-720 1.9+/-3.2	520+/-900 2.4+/-4.0	650+/-1130 2.9+/-5.0	850+/-1420 3.8+/-6.3	1020+/-1650 4.6+/-7.3
DYNAMIC FREQUENCY (HZ)	11.2	10.4	10.4	10.0	9.5	9.0
NOISE LEVEL (DBA)	<70	<70	<70	<70	<70	<70
CRATED WIDTH (IN/MM)	27 ¾ 690	29 ½ 750	29 ½ 750	30 ¼ 780	33 ¾ 860	37 940
CRATED DEPTH (IN/MM)	32 ¼ 830	35 ¾ 890	37 ¾ 950	39 ¾ 995	43 ¼ 1110	47 ¾ 1195
CRATED HEIGHT (IN/MM)	48 1219	53 ¾ 1350	53 ¾ 1350	56 ¾ 1434	61 ¼ 1556	62 ¾ 1586
CRATED WEIGHT (LB/KG)	276 126	364 166	432 169	522 238	615 280	717 326

ELECTRICAL REQUIREMENTS (STANDARD)

STANDARD VOLTAGES (V/Hz/Ø)	120 or 208 - 240 60 1					
POWER (KW) / CKT BREAKER (A) 120V	0.5 / 15	0.6 / 15	0.6 / 15	0.8 / 15	1.2 / 15	1.4 / 15
VOLTAGE/FREQUENCY/PHASE	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1
POWER (KW) / CKT BREAKER (A) 208/240V	0.4 / 15	0.5 / 15	0.5 / 15	0.7 / 15	1.1 / 15	1.3 / 15

WATER INFORMATION

INLET FITTINGS (* = 3 INLETS)	3/4 NH DN20	3/4 NH DN20	3/4 DN20	3/4* DN20*	3/4* DN20*	3/4* DN20*
FLOW (GPM/LPM @ 44 PSI) (EACH INLET)	5 20	5 20	5 20	8 30	15 60	15 60
RECOMMENDED WATER PRESSURE (PSI/KPA)	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600	30-90 200-600
MODIFIED ENERGY FACTOR	N/A					
WATER FACTOR (GAL PER CYCLE/DRUM VOLUME)	11.3	11.3	11.3	12.8	12.8	12.8

WASH FEATURES

STANDARD WASH PROGRAMS	33	33	33	33	33	33
CUSTOM WASH PROGRAMS	15	15	15	15	15	15
AVAILABLE LANGUAGES	3	3	3	3	3	3
TOP MOUNTED SOAP BOX AND REAR CHEMICAL INJECTION PORTS	•	•	•	•	•	•
NUMBER OF DETERGENT SIGNALS	5	5	5	5	5	5

