

Coin Dryers

WASCOMAT D SERIES

Precision-engineered for efficiency, ease of use, and superior drying results, **our dryers are designed to work as a system with Wascomat washers.**

Wascomat dryers have unique features that save energy, time, and money – and are your best choice for reliability, durability, and customer satisfaction.



Features and Benefits

- Optimal combination of gas consumption (Btu/hr) and airflow (CFM) provides the best-in-the-world drying performance with the fastest drying time and the lowest energy consumption
- Extra large doors make loading and unloading easy
- Easy to clean lint screen – best in the industry
- Quiet operation – Wascomat dryers are designed to keep noise level below 70 dB (A)
- Reverse drum operation minimizes tangling and wrinkling, and improves dryer efficiency
- Sturdy drum suspension with double-sealed bearings and belt drive for “workhorse” durability
- Provides unsurpassed control of temperatures, to avoid damage to linens and maximize reliability
- Axial Airflow and tight construction for extremely low energy consumption – dries faster, saving up to 25% in gas

Controls

- **Compass Pro Controller**
 - Large display for easy program selection
 - Language selection – displays two languages at one time
 - Customize programs to increase customer satisfaction

Eco-Friendly Solutions

Wascomat products are engineered for quality, energy savings, and efficiency. When you buy Wascomat, you are truly investing in the future of your business.

Reversing Drums

Reversing drums reduce energy consumption, prevents tangling, and laundry dries more quickly.

EcoPower

Save up to an additional 15% of energy consumption with EcoPower. Less wear-and-tear on garments and prevents over-drying.

Latest Styling

Choose from standard white or **NEW shiny stainless steel front panels**. New upgraded, scratch- and stain-resistant stainless steel.

LaundryPay Transforms the Laundry Experience for Your Customers

Attract new customers and build loyalty by providing the most convenient laundry service available. With our LaundryPay App, your customers can pay through their smartphone, view machine availability, and receive a notification when their wash cycle is complete.

Ultimate Control with LaundryPulse

Remotely monitor, manage, and control your business – from anywhere at any time with Laundry Pulse. Get instant service alerts, performance data, real-time revenue and utilization reports, diagnostic info, and more delivered right to your phone. You can even remotely adjust pricing and create promotional campaigns to generate business on slower days.

Wascomat “D” Series Dryers - Stack & Single Pocket	D735S		D750S		D735		D767		D783	
Capacity (lb/kg)	2 x 35	2 x 16	2 x 50	2 x 22.7	35	16	67	31	83	37.5
Width (in/mm)	31 1/8	790	34 3/16	868	28 1/16	713	37 13/16	961	37 13/16	961
Depth (in/mm)) (Steam heat add 6” (150mm) to T5x models)	43 7/8	1115	52 3/5	1336	47 5/8	1210	53 3/4	1365	61 7/16	1560
Depth with door open (in/mm) (Steam heat add 6” (150mm) to T5x models)	72 7/16	1840	85 15/16	2183	74 1/8	1883	92 1/8	2340	93 5/16	2370
Height Overall (in/mm)	76 3/8	1940	82 1/8	2086	66 1/2	1688	73 9/16	1869	73 1/8	1857
Height without heating unit (in/mm)	n/a									
Door opening diameter (in/mm)	22 13/16	580	27 1/16	687	22 5/6	580	31 7/8	810	31 7/8	810
Cylinder volume (ft3/l)	2 x 10.6	2 x 300	2 x 15	2 x 423	10.2	290	19.4	550	23.8	675
Crated Weight (lb/kg)	683	311	880	440	453	206	664	302	695	316
Utility Connections										
Exhaust duct diameter (in/mm)	8	200	8	200	8	200	8	250	8	250
Exhaust static pressure (inches H20 / mbar) (max at 60Hz)	0.75	1.9	0.75	1.9	0.75	1.9	0.75	1.9	0.75	1.9
Gas connection (One inlet supplies both pockets on stack dryers)	1/2 MNPT		3/4 MNPT		1/2 MNPT		1/2 MNPT		1/2 MNPT	
Steam connection, inlet & condensate	n/a				1 MNPT		1 MNPT		1 MNPT	
Energy Data										
Gas (Btu/hr)	2 x 71,650		2 x 94,000		71,700		112,700		143,400	
Airflow (ft3/min / m3/hr) (gas heat)	2 x 353	2 x 600	2 x 500	2 x 850	360	610	553	940	671	1140
Electric Heating Power (kW) @ 208-240V/3Ø	9 or 13.5 or 18		n/a		13.5 or 18		18 or 24 or 32		32 or 40	
Airflow (ft3/min / m3/hr) (elec. heat)	2 x 353	2 x 600			324	550	553	940	671	1140
Steam Consumption (lb/hr / kg/hr) (approximate)	n/a				80	36	118	54	150 / 68	
Airflow (ft3/min / m3/hr) (steam heat)					406	690	636	1080	812	1380
Electrical Requirements										
Current, gas or steam, 120 V/60Hz(full load/circuit breaker)	2x9A / 2x15A		2 x 14A / 2 x 20A		7.5A (15A)		15.8A (20A)		16A (20A)	
Current, gas or steam, 208-240 V/60Hz/1Ø(full load/circuit breaker)	2x4.5A / 2x15A		2 X 7A / 2 X 15A		3.8A (15A)		8.2A (15A)		8.2A (15A)	
Current, gas or steam, 208-240 V/60Hz/3Ø(full load/circuit breaker)	n/a				3.7A (15A)		10A (15A)		10A (15A)	
Current, electric, 208-240 V/60Hz/3Ø (full load/circuit breaker)	Depends upon Voltage and power selected. Contact Laundrylux Sales Department									
Alternate Voltages										
Alternate voltages available. Contact Laundrylux Sales Department.										
Supply Pressures										
Natural Gas (inches H20 / mbar)	3.5-12 / 9-30									
Propane (inches H20 / mbar)	10-13 / 25-30									
Steam (psi / bar) (max)	n/a				145 / 10					
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.										

Contact us today to learn more about our new products and technologies.

Front Panel Options



White
Standard



NEW Shiny Stainless Steel
Optional Upgrade



11/06/18

Laundrylux
800.645.2204 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010