



OPL SOFTMOUNT WASHER-EXTRACTOR

20-70 lb

Huebsch softmount washer-extractors offer smooth operation and a flexible, easy-to-install free standing design. These machines are built for durability with strong, stainless steel construction. And with 350-400 G-Force and revolutionary time-saving and utility-saving features, they're designed to improve efficiency and reduce costs – delivering 15% less water consumption than previous models. Improve your laundry performance like no other with our 20, 25, 30, 40, 55 and 70 lb capacities.

VARIABLE SPEED PERFORMANCE

Programmable wash speeds also ensure superior linen care, while high-speed extracts of 350-400 G-Force reduce drying times significantly.

EASY TO INSTALL

Because of their heavy-duty suspension systems with optimal spring and shock construction, Huebsch softmounts don't require any special foundations. That keeps installation costs low and offers flexibility to install on any floor or your building.

PROVEN FRAME DESIGN

Engineered with formed steel construction for strength and dependability.

STAINLESS STEEL CYLINDER AND OUTER TUB

Superior durability with perforated cylinder ribs for optimal mechanical wash action.

FOUR-COMPARTMENT SOAP BOX

Ergonomically designed for ease of use when manually dosing. Multiple chemical ports at the rear of the unit provide complete chemical dosing flexibility in your laundry operation.

LARGE DOOR OPENINGS

Extremely durable and offers easy loading and unloading for improved productivity.



ADVANCED HC 200 CONTROL



Features a modern, tilted control panel design with a high-resolution, multi-lingual display and offers up to 99 cycle programs. Highly flexible control with a variety of programming options available for ultimate laundry monitoring and control.

OPL SOFTMOUNT WASHER-EXTRACTORS

| Models | HY20 | HY25 | HY30 | HY40 | HY55 | HY70 | |
|--|------------------------|----------------|------------------|------------------|----------------|----------------|----------------|
| Control | HC 200 | HC 200 | HC 200 | HC 200 | HC 200 | HC200 | |
| Capacity - lb (kg) | 20 (8) | 25 (11) | 30 (14) | 40 (18) | 55 (24) | 70 (31) | |
| Width - in (mm) | 27 15/16" (710) | 31 5/16" (795) | 31 5/16" (795) | 38 3/16" (970) | 38 3/16" (970) | 38 3/16" (970) | |
| Depth - in (mm) | 31 1/8" (790) | 31 5/16" (795) | 37 3/16" (945) | 38 3/16" (970) | 43 1/2" (1105) | 46 5/8" (1185) | |
| Height - in (mm) | 43 7/8" (1115) | 48 1/4" (1225) | 48 1/4" (1225) | 55 1/2" (1410) | 55 1/2" (1410) | 55 1/2" (1410) | |
| Cylinder Diameter - in (mm) | 20 7/8" (530) | 24 3/8" (620) | 24 3/8" (620) | 29 1/2" (750) | 29 1/2" (750) | 29 1/2" (750) | |
| Cylinder Depth - in (mm) | 13 3/4" (350) | 13 3/4" (350) | 17 3/4" (450) | 16" (410) | 21 1/2" (545) | 24 1/2" (620) | |
| Cylinder Volume - cu. ft. (liters) | 2.6 (75) | 3.7 (105) | 4.8 (135) | 6.4 (180) | 8.5 (240) | 9.9 (280) | |
| Door Opening Size - in (mm) | 13" (330) | 16 1/8" (410) | 16 1/8" (410) | 18 1/8" (460) | 18 1/8" (460) | 18 1/8" (460) | |
| Door Bottom to Floor - in (mm) | 13 3/4" (349) | 13 1/2" (342) | 13 1/2" (342) | 18 3/4" (477) | 18 3/4" (477) | 18 3/4" (477) | |
| Wash Speed - RPM | 49 | 49 | 49 | 42 | 42 | 42 | |
| Extract Speed - RPM | 1165 | 1075 | 1075 | 980 | 980 | 915 | |
| Extract G-Force | 400 | 400 | 400 | 400 | 400 | 350 | |
| Water Inlet Connection - in (mm) | 2 x 3/4" (19) | 2 x 3/4" (19) | 2 x 3/4" (19) | 2 x 3/4" (19) | 2 x 3/4" (19) | 2 x 3/4" (19) | |
| Steam Inlet Connection - in (mm) | 1/2" (13) | 1/2" (13) | 1/2" (13) | 1/2" (13) | 1/2" (13) | 1/2" (13) | |
| Drain Diameter - in (mm) | 3" (76) | 3" (76) | 3" (76) | 3" (76) | 3" (76) | 3" (76) | |
| Motor Size - hp (kw) | 1.00 (.75) | 1.48 (1.10) | 2.01 (1.50) | 2.95 (2.20) | 4.02 (3.00) | 4.02 (3.00) | |
| Voltage/Hz/ Phase Circuit | 200-240V 50/60Hz 1/3ph | X | X | X | X | X | |
| | 440-480V 50/60Hz 3ph | N/A | N/A | N/A | N/A | X | |
| Shipping Dimensions Approx. - in (mm) | Width | 29 1/2" (750) | 32 7/8" (835) | 32 7/8" (835) | 40 3/8" (1025) | 40 3/8" (1025) | 40 3/8" (1025) |
| | Depth | 33 1/16" (840) | 33 1/16" (840) | 38 3/4" (985) | 40" (1015) | 45 1/4" (1150) | 48 1/4" (1225) |
| | Height | 49" (1245) | 52 15/16" (1345) | 52 15/16" (1345) | 61" (1550) | 61" (1550) | 61" (1550) |
| Net Weight - lb (kg) | 408 (185) | 463 (210) | 563 (255) | 838 (380) | 948 (430) | 1092 (495) | |
| Shipping Weight - lb (kg) | 441 (200) | 518 (235) | 606 (275) | 871 (395) | 992 (450) | 1135 (515) | |
| Agency Approvals | CSA | CSA | CSA | CSA | CSA | CSA | |

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Czech facility has been registered to ISO 14001:2005 and 9001:2009.

©Copyright 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
 Shepard Street
 Ripon, WI 54971
 1-800-553-5120
 huebsch.com

