



COIN-OPERATED DRYERS

RANGE OF SIZES • FAST, EFFECTIVE DRYING • TWO STYLE CHOICES



M330C



M50VC

Optional stainless steel panels available.

MILNOR COIN-OP DRYERS. CHOICES FOR ANY LAUNDRY!

Classic-style dryers for any application

Milnor's classic-line of coin-op dryers feature unique advantages making them ideal for new store development or replacement of older, less efficient dryers. Easy-to-use controls and fast dry times make these dryers a popular choice among coin store customers.

	Capacity Lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP (kW)	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight ins. (mm)	Electric models Oven kW	Gas model voltages
M330C	2x30 (2x14)	2x27.25 (2x692)	2x30 (2x762)	2x10.1 (2x286)	2x.3 (2x.22)	2x21.5 (2x546)	2x6 (2x152)	29.75 (756)	43.87 (1114)	78.25 (1988)	793 (360)	15	100-240V/ 1P/50,60HZ
M333C	2x30 (2x14)	2x27.25 (2x692)	2x30 (72x62)	2x10.1 (2x286)	2x.5 (2x.37)	2x21.5 (2x546)	8 (203)	29.75 (756)	52.25 (1327)	78.25 (1988)	675 (306)	N/A	120-240V/ 1P/50,60HZ
M30VC	30 (14)	32.75 (832)	25.63 (651)	12.5 (353)	.5 (.37)	21.5 (546)	8 (203)	34.25 (870)	38 (965)	72 (1828)	534 (242)	20, 24	120-480V/ 1-3P/50,60HZ
M50VC	50 (23)	32.75 (832)	37.5 (953)	18.3 (518)	.75 (.56)	21.5 (546)	8 (203)	34.25 (870)	49.75 (1264)	72 (1828)	651 (295)	20, 24, 30	100-480V/ 1-3P/50,60HZ
M758VC	75 (34)	36.25 (920)	36 (914)	21.5 (608)	1 (.75)	31.38 (797)	8 (203)	38.25 (972)	48 (1219)	75.13 (1908)	721 (327)	30	120-480V/ 1-3P/50,60HZ
M78C	75 (34)	44.5 (1130)	24.88 (632)	22.4 (634)	1 (.75)	31.38 (797)	10 (254)	46.19 (1175)	35 (889)	84.32 (2140)	888 (403)	24, 36	120-480V/ 1-3P/50,60HZ
M444C	2x45 (2x20)	2x32.75 (2x832)	2x30 (2x762)	2x14.6 (2x413)	2x.75 (2x.56)	2x27 (2x686)	2x8* (2x203)	34.31 (871)	53.31 (1350)	80.94 (2056)	905 (410)	N/A	120-240V/ 1-3P/50,60HZ
M115C	115 (52)	42 (1069)	41.25 (1048)	33.1 (937)	.75 (.56)	31.38 (797)	14 (356)	46.13 (1171)	63.56 (1614)	84 (2133)	1260 (572)	60, 72	208-575V/ 3P/50,60HZ

*Optional 10" exhausts.

Specifications and appearance subject to change without notice.

EcoDry-style dryers for best efficiency

Milnor's ED dryers deliver unmatched energy savings combined with features that provide optimal drying performance. With 100% axial airflow, heat flows in from the rear and is captured in the solid steel drum where sensors efficiently manage heat.

	Capacity Lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP (kW)	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight ins. (mm)	Electric models Oven kW	Gas model voltages
M3535EDC	2x35 (2x16)	2x30 (2x762)	2x30 (2x762)	2x12.27 (347)	2x.25 (2x.19)	2x19.38 (2x492)	2x6 (152)	31.13 (791)	39.58 (1007)	80.38 (2041)	600 (272)	7.9- 13.5	120-240V/ 1P/50,60HZ
M35EDC	35 (16)	30 (762)	30 (762)	12.27 (347)	.25 (.19)	19.38 (492)	6 (152)	31.13 (791)	40.42 (1027)	67 (1701)	462 (210)	7.9- 13.5	120-240V/ 1P/50,60HZ
M50EDC	50 (23)	37 (940)	25.75 (654)	16.02 (454)	.75 (.56)	27.38 (695)	8 (203)	38.25 (972)	40.13 (1019)	70.5 (1790)	610 (277)	13.4- 16	120-415V/ 1-3P/50,60HZ
M76EDC	75 (34)	37 (940)	35.5 (902)	22.09 (626)	.75 (.56)	27.38 (695)	8 (203)	38.25 (972)	49.81 (1265)	70.5 (1790)	745 (338)	18- 22	120-415V/ 1-3P/50,60HZ

Specifications and appearance subject to change without notice.



PELLERIN MILNOR CORPORATION
 P.O. BOX 400, Kenner, LA 70063
 504/712-7656
 Literature Hotline: 800/469-8780
 Email: mktg@milnor.com
 www.milnorcoin.com

© Pellerin Milnor Corporation. Printed in U.S.A.
 B22SL07004/19146