

Softmount Washer-Extractors

		SYT020	SYT030	SYT040	SYT055	SYT070
Control Option		Quantum Touch	Quantum Touch	Quantum Touch	Quantum Touch	Quantum Touch
Capacity - lb (kg)		20 (9)	30 (14)	40 (18)	55 (25)	70 (32)
Overall Width - in (mm)		27.95 (710)	31.29 (795)	38.18 (970)	38.18 (970)	38.18 (970)
Overall Depth - in (mm)		30.71 (780)	36.81 (935)	37.80 (960)	43.11 (1095)	46.26 (1175)
Overall Height - in (mm)		44.69 (1135)	49.02 (1245)	56.30 (1430)	56.30 (1430)	56.30 (1430)
Cylinder Diameter - in (mm)		20.87 (530)	24.40 (620)	29.53 (750)	29.53 (750)	29.53 (750)
Cylinder Depth - in (mm)		13.78 (350)	17.72 (450)	16.14 (410)	21.46 (545)	24.41 (620)
Cylinder Volume - cu. ft (liters)		2.6 (75)	4.8 (135)	6.4 (180)	8.5 (240)	9.9 (280)
Door Opening Size - in (mm)		13 (330)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)
Door Bottom to Floor - in (mm)		13.74 (349)	13.46 (342)	18.77 (477)	18.77 (477)	18.77 (477)
Water Inlet Connection - in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)
Drain Diameter - in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Height to Floor - in (mm)		3.46 (88)	3.46 (88)	4.27 (108.5)	4.27 (108.5)	4.27 (108.5)
Motor Power Consumption - HP (kW)		1 (0.75)	2.01 (1.5)	2.95 (2.20)	4.02 (3.0)	4.02 (3.0)
Wash Speed - RPM		49	49	42	42	42
Extract Speed - RPM		1165	1075	980	980	915
Extract G-Force		400	400	400	400	350
Voltage/ Circuit Breaker - FLA*	208-240/60/1	10-6.7	15-10.1	20-14.2	20-15	20-16
	440-480/60/3	-	-	-	10-7.1	10-7.2
Shipping Dimensions Approx.- in (mm)	Width	29.53 (750)	32.87 (835)	40.35 (1025)	40.35 (1025)	40.35 (1025)
	Depth	33.01 (840)	38.78 (985)	39.96 (1015)	45.28 (1150)	48.23 (1225)
	Height	49.80 (1265)	53.75 (1365)	61.81 (1570)	61.81 (1570)	61.81 (1570)
Net Weight - lb (kg)		408 (185)	563 (255)	838 (380)	948 (430)	1092 (495)
Shipping Weight - lb (kg)		441 (200)	606 (275)	871 (395)	992 (450)	1135 (515)
Agency Approvals		CSA	CSA	CSA	CSA	CSA

* Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturing strongly recommends using a circuit breaker instead of fuses.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.