



SST50 2×50 lb (25 kg)

## Maximize Time and Space

Speed Queen's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- · Supports a higher volume than typical retail and light commercial products are able to support
- · More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options



## SPEED QUEEN® ON-PREMISES LAUNDRY SOLUTIONS

## Stacked Washer-Extractor/Tumble Dryer

			SST50
		Washer-Extractor	Tumble Dryer
Control Option			PL Touch
Capacity - lb (kg)		50 (25) × 2	
Overall Width - in (mm)		34.4 (875)	
Overall Depth - in (mm)		51.3 (1302)	
Overall Height - in (mm)		84.3 (2141)	
Cylinder Diameter - in (mm)		26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)		20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)		6.3 (178)	14.8 (419)
Reversing Cylinder		-	Standard
Door Opening Size - in (mm)		16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)		14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)		2 x 0.75 (19)	-
Drain Diameter - in (mm)		1 x 3 (76)	-
Drain Height to Floor - in (mm)		4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)		-	95,000 (27.8, 100)
Gas Connection - in		-	1/2 NPT
Air Outlet - in (mm)		-	10.0 (250) Elliptical
Airflow - cfm (l/sec)		-	600 (285)
Motor - HP (kW) Fan		-	0.5 (0.4)
	Drive	2 (1.5)	0.5 (0.4)
Total # of Speeds		6	-
Cylinder Speeds - RPM (G-Force)  Wash Distribution Very Low Low Medium High Extract Very High Extract		33 (0.4)	-
		46 (0.8)	-
		82 (2.5)	-
		269 (27)	-
		464 (80)	-
		518 (100)	-
		579 (125)	-
		635 (150)	-
	gh Extract	733 (200)	<del>-</del>
Electrical Specs - amps X 200-240V/		15	10
Shipping Dimensions Approx in (mm) Width  Depth		35.5 (902)	
		54.0 (1372)	
Height No. 10 (1-2)		89.0 (2261)	
Net Weight - Ib (kg)		910 (413)	
Shipping Weight - Ib (kg)			930 (422)
Agency Approvals		<sub>c</sub> UL <sub>us</sub>	CSA

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

