



# T-SERIES WASHER-EXTRACTORS

PROGRAMMING FLEXIBILITY • TWO CAPACITIES • RINSAVE® WATER SAVER



30022 T6X

## EASY-TO-USE CONTROL



This median control with 30 programmable formulas provides flexibility and bright display allows operator to choose from real words, not codes. Standard controller features English/Spanish

(other languages optional). Controller also provides diagnostic and error messages which shorten training time of new employees and allows for fewer operator errors.



## SUPERIOR CYLINDER DESIGN

Milnor's superior cylinder design and tall, lifting ribs yield greater wash/rinse quality.

## RINSAVE® WATER SAVER FEATURE



The innovative RinSave® Water Saver feature allows a precise G-force to "sling" the wash liquor (including water, chemistry, and soil) out of the goods after a wash step – saving up to 2 rinses per load and fill/rinse time.



Scan to read more about this time, water, and energy saving feature—only available from Milnor!

## CONTINUOUSLY WELDED FRAME

Milnor frames are designed to prevent concentration of stress in one spot and all structural components are tied together for optimum stress dispersion. This proven structural integrity means your machines will last longer.




SPECIFICATIONS	30015 T6X	30022 T6X
Capacity*-lb. (kg)	40 (18)	60 (27)
Cylinder diameter-in. (mm)	30 (762)	30 (762)
Cylinder depth-in. (mm)	15 (381)	22 (559)
Door Opening-in. (mm)	15.5 (394)	15.5 (394)
Cylinder volume-cu. Ft. (L)	6.14 (174)	9 (255)
Overall width-in. (mm)	34.5 (876)	34.5 (876)
Overall depth-in. (mm)	48.62 (1234)	55.58 (1412)
Overall height-in. (mm)	56.44 (1433)	56.44 (1433)
Motor-HP (kW)	4 (2.98)	4 (2.98)
Wash Speed-RPM	38	38
Distribution Speed-RPM	65	65
Max Extract Speed-RPM	573	573
Extraction G-Force	140	140
Inlet connection-in. (mm)	0.75 (19)	0.75 (19)
Drain valve-in. (mm)	3 (76)	3 (76)
Approx gross weight-lb. (kg)	1,010 (458)	1,030 (467)

Specifications and appearance subject to change without notification. Contact the factory for acoustics data.

\*Depending on density and soil content of goods.

## DEPENDABILITY IN DESIGN



NEMA Premium® efficient inverter-driven motor



Safe chemical injection

Printed in the U.S.A.  
© Pellerin Milnor Corporation  
Brochure B22SLI4002/15063



Pellerin Milnor Corporation  
P.O. Box 400, Kenner, LA, 70063-0400 USA  
Phone: 504.712.7656 • 800.469.8780  
Fax: 504.468.3094  
Email: milnorinfo@milnor.com  
www.milnor.com