

HARDMOUNT WASHERS

THW 25 · 35 · 45 · 60



STANDARD FEATURES & BENEFITS

- Rigid mounted, medium spin
- High G-factor: 200 G
- Large door opening for easy loading and unloading
- Detergent dispenser in 4 compartments
- Standard equipped for automatic soap dosing
- Drum and tub made of robust and durable high quality stainless steel AISI 304
- Highly flexible and freely programmable control with advanced 4,3" touch control for easy operation and perfect management of your laundry business
- 8 dosing signals
- Intelligent weighing system for optimal loading
- Low water consumption
- USB connection in the front for quick data transfer
- Electronic control of imbalance with frequency control
- Loading aid feature: water and rotation control

OPTIONS

- Opposite door opening
- Coin or token version
- Stainless steel AISI 304 outer casing
- Stainless steel AISI 304 front panel
- Double drain valve
- 6 extra dosing signals
- Floor anchoring base

TOLON

HARDMOUNT WASHERS

THW 25 · 35 · 45 · 60

MODEL	UNIT	THW 25	THW 35	THW 45	THW 60				
DRUM									
Load capacity 1:9 / 1:10	Kg	28/25	39/35	47/42	67/60				
Volume	l	250	350	420	600				
Diameter	mm	770	860	860	1.048				
Depth	mm	530	602	723	684				
GENERAL DETAILS									
Washing speed/ Spinning speed	r.p.m.	40/682	45/644	45/644	42,5/505				
G-force	-	200	200	200	150				
Maximum force transmitted	KN	3,53 ±6	4,59 ±8	4,59 ±8	9,12 ±15				
Frequency-dynamic force	Hz	8,02	7,58	7,58	6,93				
Noise level	dB	<70	<70	<70	<70				
Coin laundry version	-	Yes	Yes	Yes	Yes				
Double drain	-	Opt	Opt	Opt	Opt				
Weighing system / Tilting system	-	No/No	No/No	No/No	No/No				
DOOR									
Height center door/ Height door	mm	700/400	735/440	735/440	900/540				
Diameter	mm	460	560	560	560				
POWER									
Motor	kW	3	4	6	5,5				
Electric heating power	kW	18	21	21	36				
Total electric power (electric model)	kW	19	22	23	38				
Total electric power (hw, steammodel)	kW	3	4	6	5,5				
CONNECTIONS									
		ELECTRICAL	STEAM / HOT WATER	ELECTRICAL	STEAM / HOT WATER	ELECTRICAL	STEAM / HOT WATER	ELECTRICAL	STEAM / HOT WATER
Tension 230V- I + N + T	N° x mm2 / A	-	2x1,5+T / 6A	-	2x2,5+T/ 20A	-	-	-	-
Tension 230V- III + T	N° x mm2 / A	3x16+T / 63A	-	3x16+T / 63A	-	3x16+T / 63A	-	-	-
Tension 400V- III + N + T	N° x mm2 / A	4x4+T / 32A	-	4 x6+T / 40A	-	4x6+T / 40A	4x1,5+T / 16A	4 x16+T / 63A	4x2,5+T / 20A
Steam inlet (Steam model)	inch	3/4"		3/4"		3/4"		3/4"	
Maximum steam consumption (Steam model)	Kg/h	15		18		18		21	
Water inlet	inch	3/4"		3/4"		3/4"		3/4"	
Water main pressure	Kgs/cm²	2-4		2-4		2-4		2-4	
Maximum water consumption*	Lit/h	176,1		199,6		199,66		627,9	
Drain	inch	3"		3"		3"		3"	
Drainage capacity	Lit/min	200		200		200		200	
DIMENSIONS / PACKING DIMENSIONS									
Net Width / Gross Width	mm	884/930		979/1.050		979/1.050		1.225/1.360	
Net Depth / Gross Depth	mm	965/1150		1.066/1.250		1.200/1.480		1.279/1.480	
Net Height / Gross Height	mm	1.340/1.523		1.411/1.670		1.411/1.670		1.640/1.880	
Net weight / Gross weight	kg	340/370		473/503		523/553		930/1.050	
Volume	m³	1,63		2,19		2,60		3,78	

* N°20 Program, 75% load

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

www.tolon.com

TOLON