

OPL WHITE LABEL

NAT030GN0MZAMPD0AA, NAT040GN0MZAMPD0AA, NAT055GN0MZAMPD0AA


6 Cycle Control Cabinet Hardmount Washer-Extractor

FEATURES

- 200 G-Force
- Stainless steel cylinder and tub
- Anthracite gray front and side panels
- Liquid soap connection, 4 signal soap board & top load soap box
- Large drain valve
- Front access to vital parts for easy maintenance
- 3 water inlets

LIMITED WARRANTY

- 1-Year: door seal gaskets, water valve diaphragms, belts and internal hoses
- 5-Years: frame, cylinder shaft and bearings
- 3-Years: any parts not listed above



OPL WHITE LABEL - CABINET HARDMOUNT WASHER-EXTRACTOR

SPECIFICATIONS

MODEL		NAT030GN0MZAMPD0AA*	NAT040GN0MZAMPD0AA*	NAT055GN0MZAMPD0AA*
CAPACITY - lb (kg)		30 (13.5)	40 (18)	55 (24)
OVERALL WIDTH - in (mm)		29.53 (750)	35.03 (890)	35.03 (890)
OVERALL DEPTH - in (mm)		35.43 (900)	36.02 (915)	41.73 (1,060)
OVERALL HEIGHT - in (mm)		48.22 (1,225)	55.51 (1,410)	55.51 (1,410)
CYLINDER DIAMETER - in (mm)		24.40 (620)	29.53 (750)	29.53 (750)
CYLINDER DEPTH - in (mm)		17.72 (450)	16.14 (410)	21.46 (545)
CYLINDER VOLUME - in (mm)		4.8 (135)	6.4 (180)	8.5 (240)
DOOR OPENING SIZE - in (mm)		16.14 (410)	18.11 (460)	18.11 (460)
DOOR BOTTOM TO FLOOR - in (mm)		13.46 (342)	18.31 (465)	18.31 (465)
WATER INLET CONNECTION - in (mm)		3 x 0.75 (19)	3 x 0.75 (19)	3 x 0.75 (19)
DRAIN DIAMETER - in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
DRAIN CENTER HEIGHT TO FLOOR - in (mm)		3.85 (98)	5.12 (130)	5.12 (130)
MOTOR POWER - HP (kW)		1 (0.75)	1.48 (1.1)	2.01 (1.5)
CYLINDER SPEED	Wash - RPM	46	42	42
	RPM (G-Force)	760 (200)	690 (200)	690 (200)
VOLTAGE/ CIRCUIT BREAKER - FLA	(Z) 208-240/60/1	10 - 7.2	15 - 9.1	15 - 9.2
SHIPPING DIMENSIONS APPROX. - in (mm)	Width	31.50 (800)	36.42 (925)	36.42 (925)
	Depth	37.4 (950)	38.19 (970)	44.49 (1,130)
	Height	53.35 (1,355)	61.02 (1,550)	61.02 (1,550)
NET WEIGHT - lb (kg)		419 (190)	695 (315)	728 (330)
STANDARD SHIPPING WEIGHT - lb (kg)		441 (200)	739 (335)	783 (355)
AGENCY APPROVALS		UL	UL	UL

* 7.9" base available

For the most accurate information, the installation guide should be used for all installations, design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems at Alliance Laundry Systems are registered to ISO 9001.