



Maximum Performance



## MAXIMIZE SPACE AND TIME.

UniMac's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products
- 66% more wash capacity than typical retail top load washers
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

UNIMAC.COM

**STACKED WASHER-EXTRACTOR/TUMBLE DRYERS**

# STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

SPECIFICATIONS			UST30		UST50	
			WASHER-EXTRACTOR	TUMBLE DRYER	WASHER-EXTRACTOR	TUMBLE DRYER
Control Option			OPL Touch		OPL Touch	
Capacity - lb (kg)			30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)			31.4 (797)		34.4 (875)	
Overall Depth - in (mm)			45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)			79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)			24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)			16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu ft (liters)			4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder			-	Standard	-	Standard
Door Opening Size - in (mm)			14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)			14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)			1 x 3 (76)	-	1 x 3 (76)	-
Drain Center Height to Floor - in (mm)			4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mi/hr.)			-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in			-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)			-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)			-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan		-	0.5 (0.4)	-	0.5 (0.4)
	Drive		1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds			6	-	6	-
Cylinder Speeds - RPM (G-Force)	Gentle		34 (0.4)	-	33 (0.4)	-
	Wash		48 (0.8)	-	46 (0.8)	-
	Distribution		86 (2.5)	-	82 (2.5)	-
	Very Low		282 (27)	-	269 (27)	-
	Low		485 (80)	-	464 (80)	-
	Medium		542 (100)	-	518 (100)	-
	High Extract		606 (125)	-	579 (125)	-
	Very High Extract		664 (150)	-	635 (150)	-
Ultra High Extract		766 (200)	-	733 (200)	-	
Electrical Specs - amps	X	200-240V/50/60/3	15	10	15	10
Shipping Dimensions - in (mm)	Width		34.5 (876)		35.5 (902)	
	Depth		47.0 (1194)		54.0 (1372)	
	Height		83.0 (2108)		89.0 (2261)	
Net Weight - lb (kg)			770 (349)		910 (413)	
Shipping Weight - lb (kg)			787 (357)		930 (422)	
Agency Approvals			UL <sub>us</sub>	CSA	UL <sub>us</sub>	CSA

**TO LEARN MORE, VISIT UNIMAC.COM OR CALL 1.800.587.5458. ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.