



DX13/13 | DX20/20
STACKED TUMBLE DRYER



SAFETECH FIRE SUPPRESSION SYSTEM
For maximal safety of your operations



SENSO DRY+ TECHNOLOGY
Lower energy and utility costs, lower linen replacement costs



CLOUD - BASED PLATFORM
to easily monitor your laundry everywhere and at any time



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low energy consumption and short drying time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3 - year warranty

FEATURES & BENEFITS

Features

- Standard galvanized drum
- Stainless steel front panel with black painted door
- Large door opening for easy loading & unloading
- Self cleaning lint screen

Options

- Coin operated
- Stainless steel drum
- Reversing drum

Control

- XControl FLEX PLUS - fully programmable and customizable cycles 7" touch screen.
 - User - friendly screen with operating instructions built in as part of the control
 - Complete control content available in 34 languages
- Easy - To - Use Microprocessor - Dual Digital Control or OPL Micro
- Coin Operated Easy - To - Use Microprocessor - XQ - Control (ECT)

SPECIFICATIONS

TYPE		DX13/13	DX20/20
CAPACITY			
Capacity 1:18	kg (lb)	2 x 17(38)	2 x 24(51)
Capacity 1:22	kg (lb)	2 x 14(31)	2 x 20(42)
Drum volume	l	2 x 300	2 x 420
Drum diameter	mm	Ø 762	Ø 838
AIRFLOW			
	l/sec	310 - 380	570
MOTORS			
Fan	kW	0,40	0,40
Drive	kW	0,40	0,40
NOISE LEVEL			
	dBA	63	65
GAS HEATING			
Gas connection	NPT	1/2"	1/2"
Electrical connection			
Energy per pocket	kW	16.1 - 77	23.4 - 100.2
	kBTU/h	55 - 73	80 - 95
ELECTRICAL HEATING			
Electrical connection			
Energy per pocket	kW	12 - 21	-
EXHAUST			
	mm	150 - 200	250
DIMENSIONS			
H*W*D	mm	1940x800x1100	2065x875x1260
Net weight	kg	265 - 275	315
TRANSPORT DATA			
Packed H*W*D	mm	2030x830x1190	2160x900x1370
Gross weight	kg	280 - 290	335

DIMENSIONS

	A	B	C	D	E	F	G	H	I	J	K
DX13/13	710	1245	1225	290	270	635	730	1100	695	800	1940
DX20/20	810	1280	1250	260	235	735	830	1260	770	875	2065
								depth		width	height

