

## NOTABLE FEATURES



### 3-Point Serviceability:

Designed with improved serviceability in mind. Access points on console panel, front panel and toe panel simplify maintenance.



### Inverter-Driven Motor:

Intelligent inverter measures performance, monitors motor limits and effectively balances load to ensure maximum water extraction during final spin.



### Robust A-Frame Design:

Excellent strength and stability as a result of a heavy-duty, A-frame base constructed of channel iron.



### Ergonomic Door Handle:

Rugged Easy Lock handle design boosts machine durability and provides a secure close.

# ECOWASH COMMERCIAL WASHERS



Engineered with intelligence. Designed for versatility. Built to industrial-grade standards. All to deliver durable performance beyond the everyday.

## EWR RIGID-MOUNT 200-G OPL WASHER

### RAPID-SPIN BASIC OPL MODEL NUMBERS

EWR-25M2 EWR-30M2  
EWR-40M2 EWR-60M2

### ADVANCED OPL MODEL NUMBERS

EWR-25MP2 EWR-30MP2  
EWR-40MP2 EWR-60MP2



Shown with M2 Controller



See [ADClaudry.com](http://ADClaudry.com) for full warranty details.

## ADDITIONAL FEATURES

- **Full Stainless Steel Cabinet:** Protects against corrosion and enhances machine's longevity.
- **7 External Chemical Injection Ports:** M2 Controller/4 signals, MP2 Controller/7 signals accurately dispense precise mix of chemicals at optimal time throughout the wash cycle.
- **Hinged Control Panel:** Hinged, front-panel design allows convenient, easy access to internal components eliminating the need to remove the entire console when servicing.
- **Flexible Water Level Settings:** Helps to maximize water savings and customizes wash cycles for varied applications.

A pioneering history and a prolific future. ADC, a Whirlpool Corporation brand, creates innovative, performance-built equipment to handle the trials of daily commercial laundry use. Our reliable machines continue to prove why our name has a reputation for steadfast, innovative and versatile solutions the industry counts on.

	EWR-25M2 EWR-25MP2	EWR-30M2 EWR-30MP2	EWR-40M2 EWR-40MP2	EWR-60M2 EWR-60MP2
<b>DRUM</b>				
Load Capacity (lb/kg)	25 / 10	30 / 13	40 / 18	60 / 25
Drum Volume (cu. ft./liter)	3.5 / 100	4.6 / 130	6.4 / 181	8.7 / 247
Drum Diameter (in/mm)	24 3/8 / 620	24 3/8 / 620	27 1/2 / 700	30 3/8 / 770
Drum Depth (in/mm)	13 / 330	16 7/8 / 430	18 1/2 / 470	20 7/8 / 530
<b>DIMENSIONS</b>				
Width (in/mm)	28 1/4 / 719	28 1/4 / 719	31 / 788	34 3/4 / 884
Depth (cabinet) (in/mm)	25 3/8 / 645	31 1/8 / 791	31 1/2 / 800	38 / 965
Depth (overall) (in/mm)	28 3/8 / 727	34 1/2 / 876	35 1/8 / 892	40 1/2 / 1029
Height (in/mm)	45 5/8 / 1157	45 5/8 / 1157	51 1/2 / 1307	51 7/8 / 1319
Weight (lb/kg)	467 / 212	531 / 241	622 / 282	891 / 404
<b>DIMENSIONS WITH PACKAGING</b>				
Crated Width (in/mm)	31 1/2 / 800	31 1/2 / 800	34 3/4 / 883	37 3/4 / 959
Crated Depth (in/mm)	33 1/2 / 851	40 1/2 / 1029	40 1/2 / 1029	45 3/4 / 1162
Crated Height (in/mm)	54 3/4 / 1391	54 3/4 / 1391	60 3/4 / 1543	61 1/2 / 1562
Crated Weight (lb/kg)	517 / 235	581 / 264	678 / 308	964 / 438
<b>DOOR</b>				
Height to Bottom of Door	12 1/4 / 310	12 1/4 / 310	15 5/8 / 395	17 / 433
Door Opening Diameter (in/mm)	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373
<b>POWER</b>				
Voltage / Phase (50hz or 60hz)	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH
Full Load Current / Breaker (amps)—1PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 15
Full Load Current / Breaker (amps)—3PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 15
<b>CONNECTIONS</b>				
Water Inlet (GHT/BSP)	3/4" / 3/4"	3/4" / 3/4"	3/4" / 3/4"	3/4" / 3/4"
Steam Inlet (BSP)	1/2"	1/2"	1/2"	3/4"
Drain (in/mm)	3 / 76	3 / 76	3 / 76	3 / 76
<b>CYLINDER SPEED</b>				
Washing Speed (rpm)	50	50	47	45
Spinning Speed (rpm)	760	760	760	714
G-Force	200	200	200	200
<b>WATER</b>				
Average Usage (gallons)*	18.3	29	36.8	42.6

\*One wash, two rinse cycles. No wash load.

### Intuitive Micro Controls (IMC)

The M2 Controller comes standard on ADC machines and provides a wide variety of programmable controls and cycle options. The optional MP2 Controller upgrade offers even greater customizability and control over your machine's cycles and capabilities.

#### M2 Controller (Standard)



- 10 cycle options
- Selectable water levels
- Selectable wash temperatures
- Modify cycle times in wash, rinse and spin phase
- Rapid cycle advance
- Simple diagnostic control

#### MP2 Controller (Optional Upgrade)



- 99 cycle options
- 16 standard cycles
- 83 programmable cycles
- Fully programmable cycles with computer software-enabled setup capabilities
- Rapid cycle advance
- Simple diagnostic control