

Electrolux 100 G-force Washers

N-Series, Normal Spin for Coin/Card

Electrolux washers feature Compass Pro, low water consumption, and robust design.

Electrolux Professional 100 G-Force extraction normal spin washers combine world-class reliability with innovative features and programmability.

Electrolux washers increase your productivity, lower utility costs, and provide significant electrical and gas savings. With innovative design and high performance features, Electrolux washers come standard with Compass Pro for easy customization and flexibility.

FEATURES AND BENEFITS:

- Low water and energy consumption
- Convenient four compartment detergent box
- Large, secure coin box
- Heavy-duty construction with robust steel door and lock, hinges set wide apart and door locked through entire wash cycle
- Stainless and galvanized steel in all vital parts for maximum rust protection
- SuperBalance guarantees the correct extraction force, longer machine life
- Single phase electrical for easy installation and lower costs

COMPASS PRO MICROPROCESSOR OFFERS:

- Easy to customize programs
- Large display and one control knob for easy program selection
- More than 20 languages available – displays two languages simultaneously
- Real-time clock for time-of-day pricing, happy hour pricing and promotions
- Heavy Soil and Extra Rinse option buttons for higher customer satisfaction and increased revenue
- Detailed user statistics and programmability



Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



Designed by experts. Inspired by you.

| Electrolux "N" Series, 100G Washers | W585N | | W5105N | | W5130N | | W5180N | | W5250N | | W5330N | |
|--|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|
| Capacity (lb/kg) | 20 | 9 | 25 | 11 | 30 | 14 | 45 | 20 | 62 | 28 | 77 | 35 |
| Width (in/mm) | 26 | 660 | 28 3/8 | 720 | 28 3/8 | 720 | 29 1/2 | 750 | 32 11/16 | 830 | 35 13/16 | 910 |
| Depth (overall) (in/mm) | 28 7/16 | 722 | 27 7/16 | 697 | 31 | 787 | 36 | 914 | 40 1/2 | 1029 | 43 7/8 | 1114 |
| Height (in/mm) | 44 5/8 | 1133 | 47 15/16 | 1217 | 47 7/8 | 1216 | 52 15/16 | 1345 | 56 1/8 | 1426 | 57 11/16 | 1465 |
| Height to bottom of door (in/mm) | 14 | 355 | 14 3/8 | 365 | 14 3/8 | 365 | 17 1/8 | 435 | 18 1/2 | 470 | 19 11/16 | 500 |
| Door opening diameter (in/mm) | 12 1/4 | 310 | 14 3/8 | 365 | 14 3/8 | 365 | 15 9/16 | 395 | 17 1/8 | 435 | 17 1/8 | 435 |
| Cylinder volume (ft ³ /l) | 3 | 85 | 3.7 | 105 | 4.6 | 130 | 6.4 | 180 | 8.8 | 250 | 11.7 | 330 |
| Drain outlet diameter (in/mm) | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 |
| Height to centerline of drain (in/mm) | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 |
| Extract (rpm/G-Force) | 587 / 100 | | 548 / 100 | | 548 / 100 | | 525 / 100 | | 497 / 100 | | 474 / 100 | |
| Dynamic floor load (lb/kN) | 382 +/- 697 | 1.7 +/- 3.1 | 427 +/- 562 | 1.9 +/- 2.5 | 540 +/- 697 | 2.4 +/- 3.1 | 652 +/- 877 | 2.9 +/- 3.9 | 854 +/- 1102 | 3.8 +/- 4.9 | 1034 +/- 1259 | 4.6 +/- 5.6 |
| Dynamic frequency (Hz) | 9.3 | | 9.1 | | 9.1 | | 8.8 | | 8.3 | | 7.9 | |
| Noise level (dBA) in extraction | <70 | | <70 | | <70 | | <72 | | <71 | | <74 | |
| Crated width - (in/mm) | 27 3/16 | 690 | 29 1/2 | 750 | 29 1/2 | 750 | 30 11/16 | 780 | 33 7/8 | 860 | 37 | 940 |
| Crated depth - (in/mm) | 32 11/16 | 830 | 35 1/16 | 890 | 37 3/8 | 950 | 39 3/16 | 995 | 43 11/16 | 1110 | 47 1/16 | 1195 |
| Crated height - (in/mm) | 48 | 1219 | 53 1/8 | 1350 | 53 1/8 | 1350 | 56 7/16 | 1434 | 61 1/4 | 1556 | 62 7/16 | 1586 |
| Crated weight (lb/kg) | 276 | 126 | 364 | 166 | 370 | 169 | 522 | 238 | 615 | 280 | 717 | 326 |
| Electrical Requirements (standard) | | | | | | | | | | | | |
| Voltage/frequency/phase | 208-240/60/1 or 3~ | | 208-240/60/1 or 3~ | | 208-240/60/1 or 3~ | | 208-240/60/1 or 3~ | | 208-240/60/1 or 3~ | | 208-240/60/1 or 3~ | |
| Power (kW) / Full-load current (A) / Ckt breaker (A) | 0.5 / 2.4 / 15 | | 0.7 / 3.4 / 15 | | 0.8 / 3.9 / 15 | | 0.9 / 4.3 / 15 | | 1.1 / 5.3 / 15 | | 1.2 / 5.8 / 15 | |
| Voltage/frequency/phase | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | |
| Power (kW) / Full-load current (A) / Ckt breaker (A) | 0.6 / 5.0 / 15 | | 0.8 / 5.8 / 15 | | 0.9 / 7.5 / 15 | | 1.0 / 8.3 / 15 | | 1.2 / 10.0 / 15 | | 1.3 / 10.8 / 15 | |
| Water Information | | | | | | | | | | | | |
| Inlet fittings (* = 3 inlets) | 3/4 | DN20 | 3/4 | DN20 | 3/4 | DN20 | 3/4* | DN20* | 3/4* | DN20* | 3/4* | DN20* |
| Flow (gpm/lpm @ 45 psi) (each inlet) | 5 | 20 | 5 | 20 | 5 | 20 | 5 | 20 | 16 | 60 | 16 | 60 |
| Recommended water pressure (psi/kPa) | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 |
| Approx Water usage (gal / liters @ full load) | 12.9 | 49 | 16.3 | 61.7 | 20.9 | 79 | 30.4 | 115 | 42.8 | 162 | 53.6 | 203 |
| Modified Energy Factor | n/a | | | | | | | | | | | |
| Water Factor (Gal per cycle/drum volume) | 4.3 | | 4.4 | | 4.5 | | 4.8 | | 4.8 | | 4.6 | |
| <i>Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</i> | | | | | | | | | | | | |



Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Greatest flexibility with Compass Pro®

- Real-time clock for time-of-day and happy hour pricing
- Multi-language menu selection
- Easy to customize
- Simple to use
- Revenue generating option buttons

Extended lifetime due to Super Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux
800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338
T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com
Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com
Technical Care: 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com
En Mexico: Llame gratis a este numero 001-800-010-1010