



TP SERIES 450-G
Commercial Washer-Extractor

- FWH-25 TP**
- FWH-30 TP**
- FWH-40 TP**
- FWR-60 TP**
- FWH-80 TP**

This new generation of washers combines the latest technology with the best quality in components and materials. They are equipped with the most advanced technology in water and energy saving systems, as well as the WET CLEANING feature. Its user friendly and intuitive programming makes them suitable for all types of laundries, dry- cleaners, self-service, commercial or industrial laundries, hospitals and nursery homes.

The latest features and technology at you service:

- STAINLESS STEEL DESIGN**
- EFFICIENT MIX**
- BALANCE CONTROL**
- TOUCH PLUS CONTROL**
- MULTI-CHOICE INLET**
- WET CLEANING**
- MAINT. CARE**
- OPTIMIZED DRUM**
- OPTIMAL CONSUMP.**



Powerful Flexible “Control your budget”

The laundry operator can easily program, retrieve data and create wash cycle reports through USB and laptop PC. A simple access to data bank and easy programming the TP control helps save time and ensures the correct laundry process. Trouble shooting friendly.



Built to Last Ergonomic Door System

Loading and unloading are fast and easy through the oversized ergonomic door system that opens 180 degrees. No more wasted time due to door lock error codes. Fagor maintained your laundry business running at a full productivity.



User friendly chemical dispensing

The four compartment dispenser ensures a consistent cleaning process in every wash, which it eliminate the possibility of overuse, that can result in damage fabric due to operator error.



Quality Construction and Durability

A design that offers excellent strength and stability for better performance. Washer feature inner, outer cylinder, front and side panels of durable stainless steel. Oversize bearings and housing assure superior quality & longevity over the life time of the washer.



High Speed Industrial-Commercial Strength Washer-Extractor, a Fagor Commercial product line, engineered to deliver energy efficiency, performance and to manage unmatched wash quality performance. The robust design will last for years and the performance has proven to be extremely reliable in the industry.

What makes Fagor a true commercial product and energy efficient?

MODELS	FWH-25TP	FWH-30TP	FWH-40TP	FWH-60TP	FWH-80TP
LOAD CAPACITY (lb/kg)	25 / 11	30 / 14	40 / 18	60 / 25	80 / 35
CYLINDER VOLUME (cu. ft. / liter)	3.3 / 94	4.6 / 130	6.4 / 181	8.7 / 247	14 / 350
CYLINDER DIAMETER (in / mm)	21 / 533	24 3/8 / 620	27 / 700	30 3/8 / 770	34 / 860
CYLINDER DEPTH (in / mm)	16 / 425	16 7/8 / 430	18 / 470	20 7/8 / 530	24 / 603
WIDTH (in / mm)	27 / 692	31 / 788	34 / 883	38 / 979	43.11 / 1095
DEPTH (cabinet) (in / mm)	31 1/8 / 791	31 / 800	33 / 845	38 1/4 / 973	43.86 / 1114.04
DEPTH (overall) (in / mm)	32 / 832	34 1/8 / 867	36 / 914	41 / 1041	46.61 / 1184
HEIGHT (in / mm)	45 / 1162	51 5/8 / 1310	55 5/8 / 1414	61 1/8 / 1553	62.91 / 1598
WEIGHT (lb/kg)	467 / 212	560 / 254	767 / 348	1107 / 502	1653.47 / 750
SHIPPING DIMENSIONS APPROX. - in (in / mm) with packaging					
CRATED WIDTH (in / mm)	29 / 749	33 / 857	37 / 930	41 / 1030	45.87 / 1165
CRATED DEPTH (in / mm)	39 / 997	39 / 997	41 / 1030	46 / 1168	48.43 / 1230
CRATED HEIGHT (in / mm)	56 / 1422	61 / 1568	67 / 1700	71 / 1803	75.59 / 1920
CRATED WEIGHT (lb / kg)	528 / 240	634 / 288	866 / 393	1206 / 548	1807.79 / 820
DOOR					
HEIGHT TO BOTTOM OF DOOR	16.06 / 408	16.81 / 447	19.29 / 490	24.02 / 610	20.55 / 522
DOOR OPENING DIAMETER (in / mm)	11 3/8 / 290	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	22.05 / 560
POWER					
VOLTAGE / Phase (50 hz or 60 hz)	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH	208-240 / 1 PH
Full Load Current / Breaker (amps) - 1PH	3.5 / 15	6.8 / 15	10.1 / 15	13.7 / 20	13.7 / 20
Power of Motor (Kw)	0.75	1.5	2.2	3	4
Heating Power (Electric Heating Models) (Kw)	6	9	12	18	21
Heating Power (Steam and Hot Water Heating) (Kw)	2	3	4	6	7
CONNECTIONS					
Water Inlet (GHT/BSP)	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4	3/4 / 3/4
Steam Inlet (GHT/BSP)	1/2	1/2	1/2	3/4	3/4
Drain (in / mm)	3 / 76	3 / 76	3 / 76	3 / 76	3 / 76
CYLINDER SPEED					
Washing Speed (rpm)	50	50	47	45	45
Spinning Speed (rpm)	1245	1150	1080	900	900
G-Force	450	450	450	450	450
WATER					
Average Usage (gallons)*	25	29	36.8	42.6	89.8

* Agency approvals may vary depending on configuration. Consult factory or dealer for details. For the most accurate information, please consult machine installation manual for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.

Standard Features:

- Heavy duty frame
- Stainless steel panels
- Hinged control panel
- Flexible water level setting
- 5 compartment supply dispenser
- 8 external liquid supply dispenser
- Water reuse capable
- Enclosed heavy duty drive motor
- Large door opening
- Third inlet valve
- Wet cleaning capable
- Traceability – storage of data.

Optional Features:

- Double drain kit allow the recovery of the water, with important savings.
- Drain-pump kit (25lbs and 30lbs).
- Double heating electric-steam kit.
- 6 extra signals for automatic liquid dosing.
- Industrial voltage: 440 ÷ 480 III without neutral - 50 / 60 Hz.

To learn more, or to find a distributor in your area, visit www.fagorcommercial.com

