



Greenwald pay device installation instruction for Alliance laundry MDC/Quantum machines





1. Disconnect power to machine.
2. Open control console panel.
3. Locate machine power supply transformer and disconnect output power connector.



4. Install power tap into machine connector. (installs by pushing pin in with thumb and forefinger) Polarity does not matter. Reassemble power connectors.





5. Remove coin drop harness or remove coin drop jumper.




Greenwald pay device installation instruction for Alliance laundry MDC/Quantum machines



6. Install Greenwald pay device coin harness between either the jumper or the harness removed from step 5.



7. Connect Greenwald pay communication harness into machine.



Greenwald pay device installation instruction for Alliance laundry MDC/Quantum machines




8. Make sure serial communication jumper is installed. Greenwald pay will not work without it. Previous coin operated machine will need to have this jumper installed.



Greenwald pay device installation instruction for Alliance laundry MDC/Quantum machines



9. Connect Greenwald pay device into Greenwald power conditioner and then into machine transformer from step 4 then secure the power conditioner down with some double-sided tape provided.



10. Leave console panel open and repower the machine. The Greenwald Pay device should slow blink white. Meaning not configured.
11. Follow Greenwald pay device setup instructions located in pamphlet or www.greenwaldindustries.com/gpay-help