

Vended
Galaxy™ 600
Washer-Extractors
with
eBoost™



GREAT MINDS THINK ALIKE: GALAXY™ 600 WASHER-EXTRACTORS WITH eBoost™

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in every facet of our products...

GALAXY 600 CONTROLS DESIGNED TO IMPROVE YOUR BOTTOM LINE

A VARIETY OF CYCLE SELECTIONS

Six cycle selections and multilevel pricing mean more opportunity for profit, while time-of-day pricing helps increase turns during slow times.

EXTRA WASH AND RINSE KEYS


These options enable customers to tailor wash cycles—at premium vend prices.



Cityscape



Citron



Slate

IT PAYS TO BE EFFICIENT

DISCOVER eBOOST™, OUR REVOLUTIONARY TECHNOLOGY

USES 33% LESS ELECTRICITY AND 17% LESS WATER THAN TWO-SPEED MODELS

Our advanced inverter drive technology and improved cylinder and sump system design optimize water use, while reducing non-wash water below the cylinder.

ADVANCED LEAK DETECTION ELIMINATES WASTED WATER

Patented Water Guardian™ leak detection uncovers leaks in both the drain and fill valves, eliminating wasted water—and resources.

HIGH-SPEED EXTRACTION REDUCES DRYING TIME

Our improved technology spins up to 200 G-Force, removing more water. This means shorter dry times and lower energy bills.

HUEBSCH COMMAND™

LAUNDROMAT DATA AND ANALYTICS THAT ARE CUSTOM-MADE FOR THE WAY YOU OPERATE

The Galaxy™ 600 Washer-Extractor is Huebsch Command-compatible. That means you get all features of the Galaxy control—but now you can use them remotely, from anywhere in the world with an internet connection. Huebsch Command also offers a convenient mobile app that not only delivers more flexible payment options, but also a Huebsch Rewards program to inspire greater customer loyalty to your store.



REMOTE START AND SYSTEM MONITORING



SET TIME-OF-DAY/
DAY-OF-WEEK PRICING



MULTILEVEL VEND PRICING CHANGES



ADVANCED PERFORMANCE DATA



TURNS PER DAY



100% SUPPORTED BY HUEBSCH



SERVICE ALERTS VIA EMAIL OR TEXT



CONFIGURE MACHINES FROM THE CLOUD



MOBILE APP PAYMENT FLEXIBILITY



GENERATE CUSTOMER LOYALTY WITH REWARDS

WASH, RINSE – REPEAT BUSINESS

CONVENIENCE AND TIMESAVING FEATURES THAT WILL KEEP YOUR CUSTOMERS COMING BACK

- Simple, intuitive and adjustable controls make our machines easier to operate for the end user, while flexibility in wash and rinse options increase profitability through cost adjustment.
- The ergonomically friendly door handles ensure doors will close easily and lock reliably.
- Our fill-and-forget dispenser lets customers add all their chemicals at once so they'll never forget to add bleach mid-cycle.
- Boost productivity and profits on our largest models, with fill times 43% and 20% faster on the HC60 and HC80 & 100, respectively.

BUILT TO LAST

DURABILITY MEANS LOWER COSTS AND FEWER HEADACHES.

CONTINUED INDUSTRY-LEADING PERFORMANCE

We've made our frames stronger and quieter, our proprietary inverter drive technology provides smooth, reliable power, and our seals and bearings offer seven times the water protection.

TESTED TO THE LIMIT

At Huebsch, we test our machines against the toughest standards in our state-of-the-art test lab, ensuring efficient and reliable commercial-quality machines you can trust in the field.



BACKED BY OUR 10-YEAR LIMITED WARRANTY

Our Galaxy washer-extractors with eBoost are manufactured at our Ripon, Wisconsin, headquarters. We offer an industry-leading, transferable warranty on every product:*

• Frame • Outer Tub • Cylinder • Shaft • Seals and Bearings • Bearing Housing

* Vended products only within the USA and Canada. All other markets consult with your authorized distributor.

Vended **Galaxy™ 600 Washer-Extractors** specifications

Models		HCT020	HCT030	HCT040	HCT060	HCT080	HCT100	
Control Options		Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	
Capacity – lb (kg)		20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	100 (45)	
Overall Width – in (mm)		26 (660)	29 (737)	30.6 (777)	34.1 (866)	41.5 (1054)	41.5 (1054)	
*Overall Depth – in (mm)		30.9 (785)	35.3 (897)	42.3 (1074)	44.7 (1135)	47.1 (1196)	51.1 (1298)	
Overall Height – in (mm)		43 (1092)	45 (1143)	47.2 (1199)	49.9 (1267)	57.2 (1453)	57.2 (1453)	
Cylinder Diameter – in (mm)		21 (533)	24 (610)	26.3 (668)	30 (762)	36 (914)	36 (914)	
Cylinder Depth – in (mm)		13.8 (351)	16 (406)	20.3 (516)	22 (559)	21.9 (556)	25.9 (658)	
Cylinder Volume – cu ft (liters)		2.8 (79)	4.2 (119)	6.3 (178)	9 (225)	12.9 (365)	15.2 (430)	
Door Opening Size – in (mm)		11.6 (295)	14.3 (363)	16.3 (414)	16.3 (414)	18.5 (470)	18.5(470)	
Door Bottom to Floor – in (mm)		14.4 (366)	14 (356)	14.6 (371)	14.9 (378)	17.9 (455)	17.9 (455)	
Water Inlet Connection – in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	
Drain Diameter – in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	
Drain Height to Floor – in (mm)		3.9 (99)	4.3 (109)	4.5 (114)	4.9 (124)	5.1 (130)	5.1 (130)	
Motor Power Consumption – HP(kW)		1 (0.75)	1 (0.75)	2 (1.5)	3 (2.2)	5 (3.7)	5 (3.7)	
Total # of Speeds		6, 9	6, 9	6, 9	6, 9	6, 9	6, 9	
Cylinder Speeds – RPM (G-Force)		Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	28 (0.4)
		Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)	39 (0.8)
		Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	70 (2.5)
		Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	230 (27)
		Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	396 (80)
		Medium	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)	443 (100)
		High	648 (125)	606 (125)	579 (125)	542 (125)	495 (125)	495 (125)
		Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	542 (150)
		Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)	568 (165)
** Voltage/ Circuit Breaker - FLA	B	120/60/1	15-9	15-12	20-15	N/A	N/A	N/A
	X	200-240/50-60/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
	Y	200-240/60/1/3 (Pump Drain Only)	15-4 (1 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	N/A	N/A	N/A
	N	440-480/50-60/3	15-2	15-3	15-3	15-4	15-6	15-6
Shipping Dimensions Approx. – in (mm)		Width	28 (711)	31.5 (800)	32.5 (826)	37.5 (953)	44 (1118)	44 (1118)
		Depth	33.8 (859)	38.3 (973)	43.5 (1105)	46.9 (1191)	54.5 (1384)	58.5 (1486)
		Height	49.4 (1255)	51.3 (1303)	53.6 (1361)	56.3 (1430)	59.6 (1514)	59.6 (1514)
Net Weight – lb (kg)		340 (154)	440 (200)	540 (245)	680 (308)	1250 (567)	1280 (581)	
Shipping Weight – lb (kg)		380 (172)	480 (218)	580 (263)	720 (327)	1300 (590)	1330 (603)	
Slat Crate Shipping Weight – lb (kg)		460 (209)	580 (263)	680 (308)	840 (381)	1430 (649)	1460 (662)	
***Agency Approvals		cULus	cULus	cULus	cULus	cULus	cULus	

*Overall depth includes vacuum breaker to door handle.

** Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

***Agency approvals may vary depending on configuration. Steam connection requires ½" N.P.T.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.