

Vended **Single & Stack**
Classic Tumble Dryers



VENDED SINGLE & STACK CLASSIC TUMBLE DRYERS

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in every facet of our products...

INVEST IN ADVANTAGE

HUEBSCH TUMBLE DRYERS MAXIMIZE PROFITS THROUGH SUPERIOR ENGINEERING

HIGHER CAPACITY

Efficiency means drying more loads, faster. That's how Huebsch tumble dryers are built to operate in keeping utility costs down and speeds customers through their drying cycle.

OPTIMUM EFFICIENCY

Huebsch tumble dryers feature an innovative axial airflow process, reducing energy consumption and producing some of the industry's fastest dry times. Faster drying means less time spent at the laundromat and increased customer satisfaction, loyalty and store profits.

COLLABORATIVE EFFORT

Huebsch tumble dryers are available in both single pocket and stack configurations to give your store more drying options and make the most of your space.

LESS DOWNTIME

Unlike competitors, Huebsch machines are wired individually. So if one should break down, the other unit will continue to work and more importantly, continue to make money.

QUALITY YOU CAN TOUCH

DESIGNED TO CONVEY HUEBSCH QUALITY AND ATTENTION TO DETAIL



MDC CONTROLS

Huebsch models can be configured with a programmable electronic control that delivers drying options through an intuitive user interface. A large, digital display keeps customers aware of the time remaining on their cycle.



WORKS FOR YOU

SET TO DO THE JOB AND STAYS UP TO THE TASK

DAMAGE-RESISTANT

Our patented, oblong cylinder perforations enable drywall screws forgotten in pockets to pass harmlessly through machines without damaging the tumblers' sweep sheets or a user's clothing. This damage-resistant advantage—exclusive to Huebsch machines—can be seen in action at www.huebsch.com.

LOW MAINTENANCE

Large lint compartments reduce time spent emptying and a heavy-duty belt delivers a long life to cut maintenance time and costs.

ACTIVATION VERSATILITY

All Huebsch models can be configured for coin or card activation, letting you choose the payment method that works best for your business.

UNMATCHED DURABILITY

Built with premium materials and tested to meet the demands of the harshest environments, these commercial-grade machines deliver reliable, efficient operation—and they're backed by Huebsch's standard three-year warranty.*

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



Vended **Single Classic Tumble Dryers** specifications

Models			HT025	HT030	HT055
Control Options			MDC	MDC	MDC
Capacity - lb (kg)			25 (11)	30 (14)	55 (25)
Width - in (mm)			28 (711)	28 (711)	34.5 (876)
Depth - in (mm)			40.9 (1038)	46.9 (1191)	53.6 (1362)
Height - in (mm)			63.9 (1625)	63.9 (1625)	66.8 (1695)
Cylinder Depth - in (mm)			24 (610)	30 (762)	35 (889)
Cylinder Diameter - in (mm)			26.5 (673)	26.5 (673)	33 (838)
Cylinder Volume - cu ft (liters)			7.7 (220)	9.6 (270)	17.3 (490)
Door Opening Size - in (mm)			22.7 (576)	22.7 (576)	26.9 (683)
Air Outlet - in (mm)			6 (152)	6 (152)	8 (200)
Motor - HP					
			Fan	0.25	0.25
			Cylinder	0.25	0.25
Airflow - cfm (liters/sec)					
			50 Hz	430 (203)	430 (203)
			60 Hz	500 (236)	500 (236)
Energy Data					
			Gas Models	64,000 Btu/hr	73,000 Btu/hr
			Electric Models	12 kW	21 kW
Gas Connections			0.5	0.5	0.5
Electrical Specs - amps			Gas:		
A2	100/200-220V/60/1		11.0/5.8	11.0/5.8	9.8/4.9
B2	120/208-240V/60/1		12.0/6.7	12.0/6.7	9.2/6.5
F6	200-208/240V/60/3		3.2/3.2	3.2/3.2	4.0/3.9
Q1	460-480V/60/3		1.6	1.6	-
A1	100/200V/50/1		12.1/7.5	12.1/7.5	10.0/6.2
J2	230-240V/50/1		7.5	7.5	5.5
M1	380V/50/3		-	-	2.0
N1	400-415V/50/3		-	-	2.0
M2	380/400-415V/50/3		1.5/1.6	1.5/1.6	-
			Electric:		
F5	200-208V/60/3		37	62	79
J8	240V/60/3		33	54	65
Q1	460-480V/60/3		16	27	-
J2	230-240V/50/1		58	95	119
M1	380V/50/3		20	33	43
N1	400-415V/50/3		18	31	38
Shipping Dimensions					
Approx. - in (mm)			Width	30 (760)	30 (760)
			Depth	43 (1090)	49 (1240)
			Height	69 (1753)	69 (1753)
Net Weight - lb (kg)			299 (135)	331 (150)	435 (197)
Shipping Weight - lb (kg)			332 (151)	364 (165)	476 (216)
Agency Approvals			CSA	CSA	CSA

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

Vended **Single & Stack Classic Tumble Dryers** specifications

Models		HT050	HT075	HTT30	HTT45
Control Options		MDC	MDC	MDC	MDC
Capacity – lb (kg)		50 (23)	75 (34)	2 x 30 (14)	2 x 45 (20)
Width – in (mm)		38.6 (981)	38.6 (981)	31.5 (800)	34.5 (875)
Depth – in (mm)		47 (1194)	53 (1350)	42.75 (1086)	48.6 (1235)
Height – in (mm)		76.6 (1946)	76.6 (1946)	76.25 (1937)	81 (2059)
Cylinder Depth – in (mm)		30 (762)	36 (914)	26 (660)	30 (762)
Cylinder Diameter – in (mm)		37 (940)	37 (940)	30 (762)	33 (838)
Cylinder Volume – cu ft (liters)		18.6 (528)	22.4 (634)	10.6 (300)	14.8 (420)
Door Opening Size – in (mm)		26.9 (683)	26.9 (683)	22.7 (576)	26.9 (683)
Air Outlet – in (mm)		8 (203)	8 (203)	1 x 8 (200)	1 x 10 (250)
Motor - HP					
Fan				0.5	0.5
Cylinder				0.5	0.5
Airflow – cfm (liters/sec)					
50 Hz		750 (354)	750 (354)	340 (160)	500 (236)
60 Hz			920 (434)	400 (189)	600 (283)
Energy Data					
Gas Models – Per Packet		130,000 Btu/hr	165,000 Btu/hr	73,000 x 2 Btu/hr	50 Hz - 87,000 x 2 Btu/hr 60 Hz - 95,000 x 2 Btu/hr
Electric		-		21 x 2 kW	-
Gas Connections – in (mm)		0.5	0.5	0.5	0.5
Plumbing Connections – in (mm)		0.5	0.5	-	-
Electrical Specs - amps					
Gas					
B1	120V/60/1	9.3	13.8	-	-
F3	200-208/240V/60/1	5.1/5.1	7.6/7.6	-	-
F5	200-208/240V/60/3	2.8/2.8	3.8/3.8	-	-
Q1	460-480V/60/3	1.4	1.9	-	-
J2	230-240V/50/1	6.3	6.7	-	-
M2	380/400-415V/50/3	1.6/1.6	1.8/1.8	-	-
A2	100/200-220/60/1 2W+G	-	-	22.0/11.6	-
B2	120/208-240V/60/1 2W/3W+G	-	-	16.0/8.0	-
G2	208-240V/60/1 3W+G	-	-	-	12.0
F6	200-208/240V/60/3 3W+G	-	-	6.4/6.4	9.6/9.6
A1	100/200V/50/1 2W+G	-	-	24.2/15.0	-
J2	230-240V/50/1 2W+G	-	-	15.0	10.8
Electric					
M1	380V/50/3 3W+G	-	-	33/PKT	-
N1	400-415V/50/3 3W+G	-	-	31/PKT	-
Shipping Dimensions					
Approx. – in (mm)					
Width		41.5 (1050)	41.5 (1050)	32.5 (830)	35.5 (900)
Depth		52.1 (1323)	56.4 (1433)	47 (1190)	54 (1370)
Height		81 (2057)	81 (2057)	81 (2057)	85 (2159)
Net Weight – lb (kg)		545 (247)	615 (279)	544 (247)	673 (305)
Shipping Weight – lb (kg)		602 (273)	677 (307)	582 (264)	718 (326)
Agency Approvals		CSA	CSA	CSA	CSA

