

Vended **Single & Stack**
Premium Tumble Dryers



VENDED SINGLE & STACK PREMIUM TUMBLE DRYERS

At Huebsch, our priority is making commercial laundry equipment that's perfectly aligned with your business philosophy. In other words, because you believe that profit is the inevitable result of superior efficiency, durability, simplicity and service, that's exactly what we deliver.

What's more, we deliver it in every facet of our products...

INVEST IN ADVANTAGE

HUEBSCH TUMBLE DRYERS MAXIMIZE PROFITS THROUGH SUPERIOR ENGINEERING

HIGHER CAPACITY

Efficiency means drying more loads, faster. That's how Huebsch tumble dryers are built to operate in keeping utility costs down and speeds customers through their drying cycle.

OPTIMUM EFFICIENCY

Huebsch tumble dryers feature an innovative axial airflow process, reducing energy consumption and producing some of the industry's fastest dry times. Faster drying means less time spent at the laundromat and increased customer satisfaction, loyalty and store profits.

COLLABORATIVE EFFORT

Huebsch tumble dryers are available in both single pocket and stack configurations to give your store more drying options and make the most of your space.

LESS DOWNTIME

Unlike competitors, Huebsch machines are wired individually. So if one should break down, the other unit will continue to work and more importantly, continue to make money.

A CONTEMPORARY STATEMENT PIECE

DESIGNED TO CONVEY HUEBSCH QUALITY AND ATTENTION TO DETAIL



GALAXY™ 600 CONTROLS

Integrating Galaxy™ 600 controls allows for intuitive operation and simple programming throughout your store with revenue boosting options. Better yet, it means your vended 25-, 30-, 35- and 55-lb tumble dryers are Huebsch Command™-compatible.

STEELED EXTERIORS

Huebsch's stainless-steel doors reduce chipping and incorporate durable latches and hinges to resist wear and keep machines looking sleek.

POLISHED QUALITY

Chrome handles come standard, and matching chrome doors are also available. The addition of stainless-steel front panels and cylinders gives your machines a clean, professional look. Design upgrades ensure your customers know they are using top-quality equipment.

USER-FRIENDLY

Huebsch models can be configured with a programmable electronic control that delivers drying options through an intuitive user interface. A large, digital display keeps customers aware of the time remaining on their cycle.

HUEBSCH COMMAND™

LAUNDROMAT DATA AND ANALYTICS THAT ARE CUSTOM-MADE FOR THE WAY YOU OPERATE

Huebsch Command™ (only available with Galaxy™ 600 controls) lets you use all features of Galaxy controls—and now you can access them remotely, from anywhere in the world with an internet connection. Huebsch Command also offers a convenient mobile app that not only delivers more flexible payment options, but also a Huebsch Rewards program to inspire greater customer loyalty to your store.



REMOTE START AND SYSTEM MONITORING



SET TIME-OF-DAY/
DAY-OF-WEEK PRICING



MULTILEVEL VEND
PRICING CHANGES



ADVANCED
PERFORMANCE DATA



SERVICE ALERTS VIA
EMAIL OR TEXT



CONFIGURE MACHINES
FROM THE CLOUD



TURNS PER DAY



100% SUPPORTED
BY HUEBSCH



MOBILE APP PAYMENT
FLEXIBILITY



GENERATE CUSTOMER
LOYALTY WITH REWARDS

WORKS FOR YOU

SET TO DO THE JOB AND STAYS UP TO THE TASK



DAMAGE-RESISTANT

Our patented, oblong cylinder perforations enable drywall screws forgotten in pockets to pass harmlessly through machines without damaging the tumblers' sweep sheets or a user's clothing. This damage-resistant advantage—exclusive to Huebsch machines—can be seen in action at www.huebsch.com.

LOW MAINTENANCE

Large lint compartments reduce time spent emptying and a heavy-duty belt delivers a long life to cut maintenance time and costs.

ACTIVATION VERSATILITY

All Huebsch models can be configured for coin or card activation, letting you choose the payment method that works best for your business.

UNMATCHED DURABILITY

Built with premium materials and tested to meet the demands of the harshest environments, these commercial-grade machines deliver reliable, efficient operation—and they're backed by Huebsch's standard three-year warranty.*



*Parts only, labor not included. See Huebsch Warranty Bond for specifics.

Vended **Single Premium Tumble Dryers** specifications

Models		HT025	HT030	HT035	HT055
Control Options		Galaxy™ 600	Galaxy™ 600	Galaxy™ 600, Basic Electronic	Galaxy™ 600
Dry Weight Capacity - lb (kg)		25 (11)	30 (14)	35 (16)	55 (25)
Width – in (mm)		27.9 (709)	27.9 (709)	31.5 (800)	36.4 (925)
Depth – in (mm)		39.4 (1001)	45.5 (1156)	45.5 (1156)	53.1 (1349)
Height – in (mm)		63.9 (1623)	63.9 (1623)	63.9 (1623)	66.7 (1694)
Cylinder Depth – in (mm)		24.0 (610)	30.0 (762)	30.0 (762)	35.0 (889)
Cylinder Diameter – in (mm)		26.5 (673)	26.5 (673)	30 (762)	33 (838)
Cylinder Volume – cu ft (liters)		7.7 (218)	9.6 (272)	12.3 (348)	17.3 (490)
Reversing Cylinder		Option	Option	Option	Option
Door Opening Size – in (mm)		22.7 (577)	22.7 (577)	22.7 (577)	26.9 (683)
Air Outlet – in (mm)		6 (152)	6 (152)	8 (200)	8 (200)
Motor – HP	Fan	0.3	0.3	0.3	0.5
	Cylinder	0.3	0.3	0.3	0.5
Airflow – cfm (liters/sec)		500	500	600	700
Heat Input Power	Gas Models - Per Pocket	64,000 Btu/hr	73,000 Btu/hr	90,000 Btu/hr	112,000 Btu/hr
	Steam Models - Per Pocket	83,500 Btu/hr	83,500 Btu/hr	103,400 Btu/hr	-
	Electric Models	12 kW	21 kW	24 kW	27 kW
Gas Connections – in (mm)		0.5	0.5	0.5	0.5
Plumbing Connections – Steam - in (mm)		0.75	0.75	0.75	-
Electrical Specs - amps	Gas:				
	100-120V/50/60/1	10	10	10	12
	200-240V/50/60/1/3	6	6	6	7
	440-480V/50/60/3	3	3	3	3
	380-415V/50/60/3	3	3	3	3
	Electric:				
	200-208V/50/60/1	60	104	118	133
	230-240V/50/60/1	53	90	102	116
	200-208V/50/60/3	36	61	69	78
	230-240V/50/60/3	32	52	59	67
	380V/50/60/3	19	33	37	42
	400-415V/50/60/3	18	30	34	39
	440V/50/60/3	17	29	32	37
460-480V/50/60/3	15	27	30	34	
Shipping Dimensions Approx. – in (mm)	Width	30.0 (762)	30.0 (762)	33.0 (838)	35.5 (902)
	Depth	43.0 (1092)	49.0 (1245)	49.0 (1245)	57 (1448)
	Height	67.6 (1717)	67.6 (1717)	67.6 (1717)	70.5 (1791)
Net Weight – lb (kg)	Gas & Steam	300 (136)	320 (145)	340 (154)	430 (195)
	Electric	310 (141)	330 (150)	350 (159)	440 (200)
Shipping Weight – lb (kg)	Gas & Steam	320 (145)	340 (154)	360 (163)	470 (213)
	Electric	330 (150)	350 (159)	370 (168)	480 (218)
Agency Approvals		CSA	CSA	CSA	CSA

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.

Vended **Single & Stack Premium Tumble Dryers** specifications

Models		HT050	HT075	HTT30	HTT45
Control Options		Galaxy™ 600	Galaxy™ 600	Galaxy™ 600	Galaxy™ 600
Capacity – lb (kg)		50 (23)	75 (34)	30 (14) x 2	45 (20) x 2
Width – in (mm)		38.5 (978)	38.5 (978)	31.5 (800)	34.5 (875)
Depth – in (mm)		46.8 (1189)	53.0 (1346)	42.8 (1087)	48.6 (1235)
Height – in (mm)		77.3 (1963)	77.3 (1963)	76.3 (1938)	81.3 (2065)
Cylinder Depth – in (mm)		30.0 (762)	36.0 (914)	26.0 (660)	30.0 (762)
Cylinder Diameter – in (mm)		37.0 (940)	37.0 (940)	30.0 (762)	33.0 (838)
Cylinder Volume – cu ft (liters)		18.7 (530)	22.4 (634)	10.6 (300)	14.8 (419)
Door Opening Size – in (mm)		26.9 (683)	26.9 (683)	22.6 (574)	26.9 (683)
Air Outlet – in (mm)		8 (203)	8 (203)	1 x 8 (200) Oval	1 x 10 (250) Oval
Motor - HP					
	Fan	0.5	0.5	0.3	0.5
	Cylinder	0.5	0.5	0.3	0.5
Airflow – cfm (liters/sec)		700	800	2 x 400	2 x 600
Heat Input Power					
	Gas Models – Per Packet	122,000 Btu/hr	150,000 Btu/hr	73,000 x 2 Btu/hr	95,000 x 2 Btu/hr
	Steam Models – Per Packet	113,600 Btu/hr	133,900 Btu/hr	85,400 x 2 Btu/hr	-
	Electric	30kW	36kW	21 x 2 kW	-
Gas Connections – in (mm)		0.5	0.5	0.5	0.5
Plumbing Connections – Steam - in (mm)		0.75	0.75	0.75	-
Electrical Specs - amps					
	Gas & Steam				
B	100-120V/50/60/1	9	12	16	20
X	200-240V/50/60/1/3	6	7	9	12
N	440-480V/50/60/3	3	3	6	6
P	380-415V/50/60/3	3	3	6	6
	Electric				
E	230-240V/50/60/1	91	-	-	-
F	200-208V/50/60/3	87	104	61 x 2	-
G	230-240V/50/60/3	75	90	52 x 2	-
H	380V/50/60/3	47	56	33 x 2	-
J	400-415V/50/60/3	43	52	30 x 2	-
K	440V/50/60/3	41	49	29 x 2	-
L	460-480V/50/60/3	38	45	27 x 2	-
Shipping Dimensions Approx. – in (mm)					
	Width	41.5 (1054)	41.5 (1054)	32.5 (826)	35.5 (902)
	Depth	50.0 (1270)	56.0 (1422)	47.0 (1194)	54.0 (1372)
	Height	Gas & Electric: 81.0 (2057) Steam: 83.5 (2121)	Gas & Electric: 81.0 (2057) Steam: 83.5 (2121)	79.9 (2029)	84.9 (2156)
Net Weight – lb (kg)					
	Gas	660 (299)	690 (313)	570 (259)	710 (322)
	Electric	680 (308)	720 (327)	660 (299)	-
	Steam	690 (313)	710 (322)	610 (277)	-
Shipping Weight – lb (kg)					
	Gas	710 (322)	740 (336)	600 (272)	750 (340)
	Electric	730 (331)	770 (349)	690 (313)	-
	Steam	740 (336)	760 (345)	640 (290)	-
Agency Approvals		CSA	CSA	CSA	CSA

