



## SEMI-COMMERCIAL WASHER

SC65

6 KG

## SEMI-COMMERCIAL DRYER

DAM6 - DAMC6 -

DAM6 HP

6 KG

### FEATURES

#### WASHER-EXTRACTORS

- Titanium grey cabinet
- Stainless steel drum and tub
- Easy to use timer
- Mop and medical programs
- Soap hopper at the front
- Matching dryer available – space saving when placed on top

#### DRYERS

- Titanium grey cabinet
- Stainless steel drum
- Large door opening (Ø 45 cm)

### OPTIONS

#### WASHER-EXTRACTORS

- Drain valve
- Marine voltages available

#### DRYERS

- Condens unit (DAMC6)
- Heat pump heating (DAM6 HP)
- Marine voltages available

### ACCESSORIES

#### WASHER-EXTRACTORS

- External coin meter
- Liquid soap pumps

#### DRYERS

- External coin meter



SC65



DAM6

## SC65

DRUM	
CAPACITY (KG)	6,5
DRUM VOLUME (L)	60
DIAMETER (MM)	Ø480
DRUM SPEED	
EXTRACTION SPEED (RPM)	1400
G-FACTOR	530
CONNECTIONS	
ELECTRIC (KW)	With drainpump: 208-240V/60/1 380-415V/50/3Ph+N 5 (available with drain valve) 440V/60/3Ph-N 380-415V/50/3Ph-N
ELECTRICAL HEATING (kW)	3,2
CIRCUIT BREAKER	230V-16A/400V-10A
WATER (IN)	3/4"
DRAIN	
DRAIN TYPE	Pump standard Drain valve optional
TRANSPORT DATA	
GROSS WEIGHT (KG)	77
NET WEIGHT (KG)	73
VOLUME (PACKED) (M <sup>3</sup> )	0,53
DIMENSIONS H X W X D (MM)	850 X 595 X 585
PACKING DIMENSIONS H X W X D (MM)	915 X 610 X 660

	DAM6 vented dryer	DAMC6 condense dryer	DAM6 HP heat pump dryer
DRUM			
CAPACITY (KG)	6,5	6,5	6,5
DRUM VOLUME (L)	112	112	112
DIAMETER (MM)	Ø 571	Ø 571	Ø 571
HEATING			
ELECTRIC (KW)	208-240V/60/1 380-415V/50/3Ph+N 440V/60/3Ph-N 380-415V/50/3Ph-N	380-415/50/3Ph+N	208-240V/50/1Ph
ELECTRICAL HEATING (kW)	3	2,5	1,3
CIRCUIT BREAKER	230V-16A 400V-10A		230V-10A
AIRFLOW (M <sup>3</sup> /H)	123	245	internal
AIR EVACUATION	100	-	-
TRANSPORT DATA			
GROSS WEIGHT (KG)	42	46	54
NET WEIGHT (KG)	39	47	52
VOLUME (PACKED) (M <sup>3</sup> )	0,53	0,53	0,53
DIMENSIONS H X W X D (MM)	850 X 595 X 585	850 X 595 X 585	850 X 595 X 585
PACKING DIMENSIONS H X W X D (MM)	915 X 610 X 660	915 X 610 X 660	915 X 610 X 660

