



HIGH-EFFICIENT SOFTMOUNT WASHER-EXTRACTORS

IY65

6,5KG

IY80

8KG

IY105

11KG

IY135

14KG

FEATURES

- Freestanding, high spin (up to 1165 rpm - IY65, IY80)
- Stainless steel top and front panel, black side panels
- Stainless steel drum and tub
- Aries - easy to use microprocessor
- Patented soap hopper
- Large drain valve (Ø 76 mm)
- Easy access to all vital parts from the front
- Large door opening for easy loading & unloading

OPTIONS

- Aries Elite - Fully programmable
- Coin operated
- Stainless steel side panels
- USB plug (on the back panel)
- Liquid soap connection
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump (IY65, IY80)
- 3rd water inlet



ERGONOMICAL
CONSTRUCTION



LARGE DOOR
OPENING



LOW WATER
CONSUMPTION



LOW ENERGY
CONSUMPTION

THE SMART LAUNDRY PARTNER

	IY65	IY80	IY105	IY135
INNERDRUM				
CAPACITY 10:1 (KG)	6,5	8	11	14
CAPACITY 9:1 (KG)	7	9	12	15
VOLUME (L)	65	75	105	135
DIAMETER (MM)	530	530	620	620
DRUM SPEED				
WASH (RPM)	49	49	49	49
EXTRACTION (RPM)	1086 (350G) 1165 (400G)	1086 (350G) 1165 (400G)	1005 (350G) 1075 (400G)	1005 (350G) 1075 (400G)
G-FACTOR	350 (optional 400)	350 (optional 400)	350 (optional 400)	350 (optional 400)
HEATING				
ELECTRICITY (KW)	6	6	9	12
STEAM (BAR)	1 - 8	1 - 8	1-8	1 - 8
HOT WATER (°C)	90	90	90	90
SOUND PRESSURE LEVEL (DB) (A)	< 65	< 65	< 65	< 65
WATER VALVES CONNECTION (BSP)	3/4"	3/4"	3/4"	3/4"
WATER PRESSURE (KPA)	100-800	100-800	100-800	100-800
REC. WATER PRESSURE (KPA)	300-500	300-500	300-500	300-500
WATER INLET (L/MIN)	20	20	20	20
DRAIN VALVE OUTER (MM)	Ø 76	Ø 76	Ø 76	Ø 76
FLOW AMOUNT WITH DRAIN VALVE (L/MIN)	210	210	210	210
STEAM VALVE CONNECTION (BSP)	1/2"	1/2"	1/2"	1/2"
STEAM PRESSURE (KPA)	100-800	100-800	100-800	100-800
TRANSPORT DATA				
GROSS WEIGHT (KG)	180	200	235	275
NET WEIGHT (KG)	170	185	210	255
PACKING DIMENSIONS H x W x D (MM)	1245 x 750 x 840	1245 x 750 x 840	1345 x 835 x 840	1345 x 835 x 985

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
IY65	710	740	1115	676	349	230	82	914	1004	113	218	293	390	1020	24
IY80	710	790	1115	726	349	230	88	920	1010	113	218	293	390	1020	24
IY105	795	795	1225	761	342	230	88	1030	1120	103	208	293	475	1130	24
IY135	795	945	1225	911	342	230	88	1030	1120	103	208	293	475	1130	24
	width	depth	height												

	IY80
Water consumption	7,2 L/KG
Electricity consumption	0,19 kW/kg

*Program nr 11

