

# MAYTAG ENGINEERED MAYTAG ENGINEERED MAYTAG MULTI-LOAD

### INTRODUCING THE MULTI-LOAD WASHER



## FOR VENDED LAUNDRY



## **CONNECTED FOR EFFICIENCY**

Maytag Connect 360<sup>o™</sup> Technology\* keeps you up to date with the performance of every machine – to help ensure your operation is running efficiently at all times.



#### MAYTAG CONNECT 360°™ TECHNOLOGY

With a WiFi-enabled system, Maytag Connect 360<sup>o™</sup> Technology\* gives owners the ability to manage their stores in real-time, even when away. Our intuitively designed software provides diagnostics, notifications, and revenue reports– to keep each machine working at full capacity.

#### **POWERFUL ONLINE TOOLS**

Receive select diagnostics and alerts for preventative maintenance, and make program changes remotely – via WiFi – or on-site with our USB port.



#### SERVICE NOTIFICATIONS

Receive alerts for select service and maintenance issues – to help identify where the problem exists, so technicians can come prepared to repair the washer in timely fashion.



#### 24/7 ACCESS TO INSIGHTS

Owners have access to every machine's information – to better understand, prevent, and solve performance issues, and maximize investment return.

#### OVER-THE-AIR UPDATES

Software upgrades can be made automatically through the WiFi-enabled board or with USB port – keeping every machine constantly updated with the latest technology from Maytag.





MODEL	MYS20PD	MYS30PD	MYS40PD	MYS55PD	MYS65PD
MOTOR					
Size – HP	1.0	2.0	3.0	4.0	4.0
CAPACITY					
Cylinder Volume – cu. ft. (liters)	2.74 (78)	4.86 (138)	6.45 (183)	8.56 (242)	9.76 (276)
Cylinder Diameter – in. (mm)	20.9 (530)	24.4 (620)	29.5 (750)	29.5 (750)	29.5 (750)
Cylinder Depth – in. (mm)	13.9 (352)	17.9 (454)	16.2 (411)	21.6 (548)	24.4 (621)
Dry Load Capacity – Ib. (kg)	20 (9)	30 (14)	40 (18)	55 (25)	65 (30)
EXTRACT FORCE					
Maximum Extract Force (G-force)	400	400	400	400	350
CONNECTIVITY					
USB Programmability	Yes	Yes	Yes	Yes	Yes
Maytag Connect 360°™ Technology* Ready	Yes	Yes	Yes	Yes	Yes
DIMENSIONS	100	100	100	100	100
Depth – in. (mm)	28.4 (720)	34.3 (872)	35.5 (901)	40.8 (1,036)	43.7 (1,110)
Width – in. (mm)	28.0 (711)	31.3 (794)	38.2 (970)	38.2 (970)	38.2 (970)
Height – in. (mm)	43.8 (1,112)	48.1 (1,222)	55.5 (1,410)	55.5 (1,410)	55.5 (1,410)
Door opening – in. (mm)	12.9 (328)	16.1 (410)	18.1 (459)	18.1 (459)	18.1 (459)
CRATED DIMENSIONS	12.3 (020)	10.1 (410)	10.1 (400)	10.1 (400)	10.1 (403)
	00.8 (756)	33.1 (841)	39.5 (1,003)	20 E (1 002)	$20 \in (1, 002)$
Width – in. (mm)	29.8 (756)	, ,	. , ,	39.5 (1,003)	39.5 (1,003)
Depth – in. (mm)	33.6 (854)	39.8 (1,010)	41.0 (1,042)	46.4 (1,178)	49.3 (1,251)
Height – in. (mm) APPROXIMATE WEIGHT	50.0 (1,270)	54.4 (1,381)	61.4 (1,560)	61.4 (1,560)	61.4 (1,560)
	445 (400)	500 (00 ()	054 (000)		0.4.4 (40.0)
Uncrated – Ib. (kg)	415 (188)	582 (264)	851 (386)	894 (406)	944 (428)
Crated – Ib. (kg)	446 (202)	616 (279)	889 (403)	933 (423)	984 (446)
Full Truck (53' / 48')	60 / 54	38 / 34	32 / 28	32 / 28	32 / 28
40' HC Container	42	28	24	22	21
20' Container	18	14	10	10	9
ELECTRICAL CONNECTION OPTIONS (VOLT					
W = 120 / 60 / 1 (no electrical heating)	Yes	Yes	No	No	No
T = 208 - 240 / 50 - 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes
S = 220 - 240 / 50 - 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes
V = 208 - 240 / 50 - 60 / 3	Yes	Yes	Yes	Yes	Yes
N = 380 - 415 / 50 - 60 / 3	Yes	Yes	Yes	Yes	Yes
R = 440 - 480 / 50 - 60 / 3	Yes	Yes	Yes	Yes	Yes
WATER HEATING OPTIONS					
Hot/Cold Water Connections Only	Yes	Yes	Yes	Yes	Yes
Electrical Heating (size of heating elements, kW)	Yes (8)	Yes (12)	Yes (16)	Yes (18)	Yes (18)
Electrical Heating, Optional Alternate	12	8	N/A	N/A	N/A
Heating Element Size- kW	12	0	N/A		11/7
Steam Kit Option	N/A	N/A	Yes	Yes	Yes
WATER, CHEMICAL DISPENSING, DRAINS					
Number of Water Inlets	2	2	2	2	2
Optional Third Water Inlet	Yes	Yes	Yes	Yes	Yes
Inlet Sizes – in. (mm)	<sup>1</sup> / <sub>2</sub> (13)	<sup>3</sup> / <sub>4</sub> (19)			
Operating Pressure – PSI (bar)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)
Number of Dispenser Compartments	4	4	4	4	4
External Chemical Connections, Number	10	10	10	10	10
Dump Valve Drain, Size in. (mm)	Yes, 3 (76)				
Second Dump Valve Drain Option	No	No	No	Yes	Yes
Drain Pump Option	Yes	Yes	Yes	No	No
SOUND PRESSURE – dbA	<70	<70	<70	<70	<70

\*WiFi required. Features subject to change. Details and privacy info at connect360.maytag.com. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.