

# Washer Extra Dry

## WASCOMAT WED SERIES

Combining world-class reliability with innovative features and programmability, **Wascomat washers are designed to work as a system with Wascomat dryers.** The washer initiates the drying process which means, the higher the G-force, the more water is extracted from the laundry. This speeds up the drying process, saving energy, time, and money.



### Wascomat WED Washers continue a long tradition of excellence in technology, design, and quality.

- Automatic Savings (AS) determines the exact load weight and adds precisely the right amount of water for significant savings
- Compass Pro lets you control important functions such as exact water levels, wash times and number of rinses – with a simple turn of the dial
- Robust door handle – durable in any environment
- Door unlocks immediately at the end of final cycle – no delays
- Unique 4-compartment supply dispenser
- Extended machine life with Super Balance
- Sanitizing Rinse generates customer loyalty, gives customers peace of mind
- Text messaging and voice guidance features (optional)
- Innovative LaundryPulse and LaundryPay (optional)
- Interchangeable parts from one machine size to another

### Features and Benefits

**Wascomat Compass Pro provides the ultimate in flexibility:**

- Create fully customized wash programs to lower costs and meet customer demands for your specific market
- Cycle upgrade options increase store revenue and boost customer satisfaction
- Display wash program information in multiple languages
- Real-time clock for happy hour, promotional pricing

### Eco-Friendly Solutions

Wascomat products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

### Latest Styling

Choose from standard white or **NEW shiny stainless steel front panels.** New upgraded, scratch- and stain-resistant stainless steel.

### Perfect Fit


Most sizes available in 220 or 120 volt, single phase. Now it's easy to replace old, inefficient top-load or front-load washers with new Wascomat equipment.

### LaundryPay Transforms the Laundry Experience for Your Customers

Attract new customers and build loyalty by providing the most convenient laundry service available. With our LaundryPay App, your customers can pay through their smartphone, view machine availability, and receive a notification when their wash cycle is complete.

### Ultimate Control with LaundryPulse

Remotely monitor, manage, and control your business – from anywhere at any time with Laundry Pulse. Get instant service alerts, performance data, real-time revenue and utilization reports, diagnostic info, and more delivered right to your phone. You can even remotely adjust pricing and create promotional campaigns to generate business on slower days.



Wascomat "WED" Series Washers	WED720		WED725		WED730		WED745		WED762		WED777	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	28 7/16	722	27 7/16	697	31	787	36	914	40 1/2	1029	43 7/8	1114
Height (in/mm)	44 5/8	1133	47 15/16	1217	47 7/8	1216	52 15/16	1345	56 1/8	1426	57 11/16	1465
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 1/4	310	14 3/8	365	14 3/8	365	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft <sup>3</sup> /l)	3	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103
Extract (rpm/G-Force)	830 / 200		776 / 200		776 / 200		742 / 200		702 / 200		641 / 200	
Dynamic floor load (lb/kN)	382 +/- 585	1.7 +/- 2.6	427 +/- 674	1.9 +/- 3	517 +/- 854	2.3 +/- 3.8	674 +/- 1079	3 +/- 4.8	854 +/- 1326	3.8 +/- 5.9	967 +/- 1551	4.3 +/- 6.9
Dynamic frequency (Hz)	13.8		12.9		12.9		12.4		11.7		11.2	
Noise level (dBA) in extraction	<75		<71		<72		<74		<76		<75	
Crated width - (in/mm)	27 3/16	690	29 1/2	750	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	32 11/16	830	35 1/16	890	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	48	1219	53 1/8	1350	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Crated weight (lb/kg)	276	126	364	166	370	169	522	238	615	280	717	326
<b>Electrical Requirements (standard)</b>												
Voltage/frequency/phase	208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/1 or 3-		208-240/60/1 or 3-	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.5 / 2.4 / 15		0.7 / 3.4 / 15		0.8 / 3.9 / 15		0.9 / 4.3 / 15		1.1 / 5.3 / 15		1.2 / 5.8 / 15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		120/60/1	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.6 / 5.0 / 15		0.8 / 5.8 / 15		0.9 / 7.5 / 15		1.0 / 8.3 / 15		1.2 / 10.0 / 15		1.3 / 10.8 / 15	
<b>Water Information</b>												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	10.8	41	14.3	54	16.5	62	23.7	90	32.7	124	43.5	165
Modified Energy Factor	2.1		2.1		2.2		2.3		2.0		2.0	
Water Factor (Gal per cycle/drum volume)	4.0		3.9		3.9		4.0		4.0		4.0	
Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.												

**Contact us today to learn more about our new products and technologies.**

#### Front Panel Options



**White**  
Standard



**NEW Shiny Stainless Steel**  
Optional Upgrade



## Laundrylux

**800.645.2204 • laundrylux.com**

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

**Sales & Administration:** 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

**Parts:** 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

**Tech Support:** 516-371-0700 • F 516-371-4029 • service@laundrylux.com

**En Mexico:** Llame gratis a este numero 001-800-010-1010